

## Photometric test report

Family  
Ecopack® 31

Order number: 51LJ12DKM40A  
EAN: 4058352589519

LP number  
59348\_14



**Version** diffuser optic, frosted, polycarbonate,  
adjustable color temperature: 3000K | 4000K |  
5000K, extremely wide distribution

**Lamps** LED 5000 K | CRI ≥ 80

**Controlgear** ECG-DALI

**Setting** individual position: colour temperature 5000K

**Rated values** Net luminous flux = 4290 lm  
Power consumption = 33.0 W  
Luminous efficacy = 130 lm/W

serial  
documentation  
19.08.2022


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 248 cd/klm



### Classifications

DIN 5040 B 3 1  
CIE N1=39 N2=67 N3=87  
N4=89 N5=100

### Luminaire light output ratios

$\eta_{LB}$  100.0%  
 $\phi_u$  88.8%  
 $\phi_o$  11.2%

### Measurement conditions

DIN EN 13032 and DIN 5032

## Photometric test report

Family <b>Ecopack® 31</b>	Order number: <b>51LJ12DKM40A</b> EAN: <b>4058352589519</b>	LP number <b>59348_14</b>
Table of values for luminous intensities		Maximum luminous intensity
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
0°	248.4	248.4	248.4	248.4	248.4	248.4	248.4	1.5	1.5
5°	247.8	248.0	248.2	247.6	247.0	246.9	246.9	11.8	13.3
10°	245.6	246.0	246.3	244.9	243.5	243.3	243.2	23.3	36.6
15°	241.9	242.3	242.7	240.5	238.4	237.7	237.0	34.1	70.7
20°	236.8	237.0	237.1	234.0	230.9	229.5	228.1	43.8	114.5
25°	230.3	230.4	230.5	226.1	221.8	219.5	217.2	52.2	166.7
30°	222.7	222.6	222.5	216.9	211.3	208.2	205.1	59.2	225.8
35°	213.3	213.1	212.8	205.7	198.6	194.5	190.3	64.3	290.1
40°	203.4	202.9	202.5	193.9	185.3	180.1	175.0	67.8	357.8
45°	192.7	192.1	191.5	181.3	171.1	164.6	158.1	69.5	427.3
50°	180.4	179.6	178.8	167.2	155.7	147.7	139.7	69.2	496.6
55°	168.3	167.2	166.2	153.2	140.3	130.9	121.5	67.6	564.1
60°	155.7	154.5	153.3	139.2	125.1	113.8	102.5	64.5	628.6
65°	142.1	141.2	140.3	124.9	109.4	96.4	83.4	60.0	688.6
70°	129.3	128.0	126.8	110.8	94.9	78.6	62.2	54.5	743.1
75°	116.5	115.1	113.8	97.8	81.8	65.0	48.3	49.1	792.2
80°	104.3	102.8	101.4	86.0	70.6	51.1	31.7	43.2	835.4
85°	91.9	90.5	89.2	73.8	58.4	38.0	17.7	36.8	872.2
90°	81.5	79.6	77.8	62.8	47.8	28.4	9.1	31.2	903.4
95°	70.6	66.3	62.0	50.4	38.9	22.1	5.3	25.3	928.7
100°	56.2	54.3	52.5	39.2	26.0	14.7	3.5	19.5	948.1
105°	50.3	48.5	46.6	34.6	22.7	12.9	3.1	16.9	965.1
110°	43.2	41.8	40.4	29.8	19.3	11.1	2.9	14.2	979.3
115°	36.9	35.3	33.8	24.8	15.9	9.4	2.8	11.5	990.8
120°	31.0	29.8	28.6	20.6	12.7	7.7	2.6	9.2	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

Family <b>Ecopack® 31</b>	Order number: <b>51LJ12DKM40A</b> EAN: <b>4058352589519</b>	LP number <b>59348_14</b>
------------------------------	--	------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.7	22.4	21.1	22.8	23.2	20.2	21.9	20.6	22.2	22.7
	3H	22.7	24.3	23.2	24.7	25.2	21.8	23.4	22.2	23.8	24.2
	4H	23.7	25.1	24.2	25.6	26.1	22.5	24.0	23.0	24.4	24.9
	6H	24.7	26.0	25.2	26.5	27.0	23.1	24.5	23.6	24.9	25.4
	8H	25.2	26.4	25.7	26.9	27.4	23.3	24.6	23.8	25.1	25.6
	12H	25.6	26.7	26.1	27.3	27.8	23.5	24.7	24.0	25.2	25.8
4H	2H	21.4	22.9	21.9	23.3	23.8	21.0	22.4	21.5	22.9	23.4
	3H	23.7	25.0	24.2	25.5	26.0	22.9	24.1	23.4	24.6	25.1
	4H	24.9	26.0	25.4	26.5	27.1	23.7	24.9	24.3	25.4	26.0
	6H	26.0	27.0	26.5	27.5	28.1	24.5	25.5	25.1	26.1	26.7
	8H	26.6	27.5	27.1	28.0	28.7	24.9	25.8	25.4	26.4	27.0
	12H	27.1	27.9	27.7	28.5	29.1	25.1	25.9	25.7	26.5	27.2
8H	4H	25.3	26.2	25.8	26.8	27.4	24.3	25.3	24.9	25.8	26.4
	6H	26.7	27.5	27.3	28.1	28.7	25.4	26.2	26.0	26.8	27.4
	8H	27.4	28.1	28.0	28.7	29.4	25.8	26.6	26.5	27.2	27.8
	12H	28.0	28.6	28.7	29.3	30.0	26.2	26.9	26.9	27.5	28.2
12H	4H	25.3	26.2	25.9	26.8	27.4	24.4	25.2	25.0	25.8	26.5
	6H	26.8	27.5	27.4	28.1	28.8	25.6	26.3	26.2	26.9	27.6
	8H	27.6	28.2	28.2	28.8	29.5	26.1	26.8	26.8	27.4	28.1

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm:</b>	<b>L = 1142</b>	<b>H(C0) = 29</b>	<b>H(C180) = 29</b>
			<b>B = 56</b>	<b>H(C90) = 0</b>	<b>H(C270) = 0</b>

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		12043.3	12145.8	12539.0	12588.9	12895.8	13769.5	14995.1	
50°		11640.8	11741.2	12157.8	12149.3	12415.5	13288.0	14574.2	
55°		11312.9	11407.7	11846.6	11768.3	11980.7	12852.0	14213.1	
60°		11010.5	11105.0	11575.1	11425.6	11583.3	12391.4	13757.9	
65°		10689.4	10815.2	11353.5	11101.9	11166.6	11888.0	13242.6	
70°		10463.6	10574.8	11139.2	10836.8	10876.5	11262.6	12206.0	
75°		10293.6	10409.3	11031.6	10708.1	10775.5	11237.1	12527.6	
80°		10230.7	10353.5	11054.8	10796.8	11045.6	11218.6	12227.0	
85°		10221.7	10372.9	11203.4	10948.3	11342.5	11556.7	13612.5	

**Photometric test report**

Family <b>Ecopack® 31</b>	Order number: <b>51LJ12DKM40A</b> EAN: <b>4058352589519</b>	LP number <b>59348_14</b>
------------------------------	--	------------------------------

Luminance values in cd/m<sup>2</sup>     γ 65°   γ 70°   γ 75°   γ 80°   γ 85°     **siteco**

