

Photometric test report

Family
MUSHROOM LUMINAIRE LED



Order number: **5XA5235MF14H + 5XA54000XBS**
EAN: **4058352833247 + 4050737971445**

LP number
59054_23

serial
documentation
04.11.2022

Version post-top- or mounting to wall arm, shielding on building side
Optic asymmetric, wide distribution (ST1.2a)
Cover cover transparent, PMMA
Lamps LED 2700 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 1540 lm
Power consumption = 11.8 W
Luminous efficacy = 130.5 lm/W

siteco

Luminous intensity in cd/klm


C180-0

C205-25

C210-30

C270-90

Imax: 762 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	97.4%
Eta 90° - 180°	2.6%

Luminous intensity class acc. to EN13201-2

Class:	G1
Imax 70°	701.8
Imax 80°	155.9
Imax 90°	12.0
Imax >90°	11.5
Imax >95°	9.4


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
---	--	------------------------------

Envelope curve in cd/klm **KMK 67.5°** **KMK 65°** **KMK 62.5°** **KMK 60°**



Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1
2,5°	31.3	30.8	32.9	35.5	37.9	39.7	40.2	40.2	39.4	39.2	39.7	40.0	40.0
5,0°	50.9	51.5	58.5	60.1	61.6	56.7	55.1	53.0	52.0	54.3	58.2	61.9	61.6
7,5°	64.2	69.7	71.0	69.5	66.3	72.3	78.4	86.2	89.3	95.1	95.3	96.4	94.8
10,0°	80.2	86.7	92.7	100.0	114.4	124.8	123.8	115.2	111.8	118.3	123.8	134.5	140.0
12,5°	102.6	104.5	115.4	120.4	116.7	121.4	127.2	134.0	144.2	157.8	170.8	172.6	180.5
15,0°	105.5	124.1	166.6	173.2	150.2	159.3	184.7	205.8	217.0	200.1	198.0	195.9	204.2
17,5°	150.4	130.8	153.6	172.9	173.4	190.4	185.2	187.3	196.4	199.8	210.2	212.6	222.3
20,0°	149.9	178.1	189.1	187.3	191.4	186.2	191.7	193.0	193.0	205.0	208.2	216.3	214.2
22,5°	157.5	174.2	182.0	192.7	200.6	212.1	210.5	207.4	196.9	193.0	206.6	223.0	233.0
25,0°	161.9	168.5	186.7	196.4	193.3	199.5	213.4	217.6	207.9	200.1	203.5	217.3	241.6
27,5°	179.2	178.9	189.1	216.5	205.8	207.6	218.6	240.3	246.8	240.8	239.8	241.1	262.0
30,0°	186.5	225.1	215.7	216.8	213.9	207.9	214.9	223.6	246.3	262.7	261.2	258.6	277.4
32,5°	182.3	194.3	192.7	210.8	224.4	243.7	249.2	263.8	272.4	295.4	309.8	310.3	307.9
35,0°	227.0	242.4	237.7	243.9	242.4	257.8	283.4	291.7	294.6	304.5	332.5	346.8	332.0
37,5°	233.5	251.5	256.5	264.3	266.4	261.4	273.2	316.8	335.9	332.7	346.3	374.3	369.3
40,0°	251.3	251.0	255.7	269.8	295.4	303.5	309.8	333.3	351.5	377.4	369.3	382.9	395.7
42,5°	265.9	259.3	278.9	283.1	309.0	318.4	350.8	365.9	365.4	397.8	403.5	394.1	409.0
45,0°	275.5	277.6	313.7	318.4	335.9	338.0	356.2	401.2	408.2	409.3	423.9	419.4	421.3
47,5°	282.1	289.9	357.0	373.7	393.3	365.1	404.8	426.5	436.4	427.5	438.3	440.9	428.3
50,0°	286.0	295.7	408.0	404.0	470.6	412.1	476.4	484.2	437.5	428.6	448.2	444.8	423.1
52,5°	293.3	306.6	422.3	410.3	515.3	493.9	523.7	537.2	465.4	432.5	453.1	453.4	423.9
55,0°	298.8	327.8	411.9	457.3	560.5	578.8	583.7	562.8	502.8	445.8	454.2	445.6	401.7
57,5°	306.6	363.3	445.8	511.1	637.3	666.5	621.3	564.4	524.7	452.6	434.1	418.1	370.6
60,0°	268.2	356.2	471.4	559.7	670.4	708.3	621.3	584.3	534.6	449.5	408.2	380.3	327.3
62,5°	217.6	325.2	452.1	561.8	668.9	714.3	634.1	618.5	567.5	446.6	390.2	354.4	291.7
65,0°	185.4	275.5	414.2	483.2	582.4	745.9	715.9	633.4	544.6	448.4	380.0	333.8	254.4
67,5°	166.1	251.8	391.2	416.6	535.2	762.1	747.2	594.2	541.2	422.6	342.7	297.5	219.4
70,0°	189.4	283.6	418.1	442.2	495.7	692.6	701.8	574.1	488.4	388.4	319.9	264.0	178.6
72,5°	203.2	322.0	415.0	440.3	492.1	604.9	620.0	502.0	384.7	322.0	258.8	215.7	143.6
75,0°	146.0	292.8	367.5	379.0	446.9	503.3	526.8	370.6	266.4	211.3	208.7	188.3	124.6
77,5°	126.1	205.0	232.4	271.9	299.3	289.9	294.9	206.6	164.3	149.7	152.0	147.0	106.3
80,0°	75.5	88.5	101.6	139.5	142.1	135.8	155.9	145.5	115.7	82.0	63.7	69.0	46.5
82,5°	46.2	49.4	51.2	71.0	76.8	56.9	77.3	99.0	78.9	48.8	34.5	24.3	17.0
85,0°	21.9	23.5	23.2	25.3	20.6	26.6	42.6	49.6	30.3	23.8	15.9	15.1	14.1
87,5°	11.8	12.0	12.3	12.5	12.8	13.1	13.6	13.3	13.3	13.1	13.1	13.1	12.8
90,0°	10.4	11.0	11.0	11.5	11.5	11.8	12.0	12.0	12.0	12.0	12.0	11.5	11.0
92,5°	9.4	9.9	10.2	10.4	10.4	11.0	11.2	11.5	11.5	11.0	10.4	10.4	10.4
95,0°	8.9	9.1	9.4	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.7
97,5°	8.6	8.6	8.9	9.1	9.1	9.1	9.4	9.4	9.4	9.4	9.4	9.4	9.1
100,0°	8.1	8.4	8.4	8.6	8.6	8.6	8.9	8.6	8.6	8.9	8.9	8.6	8.6
102,5°	7.8	8.1	8.1	8.1	8.1	8.1	8.4	8.4	8.4	8.4	8.4	8.4	8.4
105,0°	7.3	7.6	7.6	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8
107,5°	6.8	7.1	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
110,0°	6.8	6.8	6.8	6.8	7.1	7.1	7.1	7.1	7.3	7.3	7.3	7.3	7.3
112,5°	6.3	6.3	6.5	6.5	6.5	6.5	6.8	6.8	6.8	6.8	6.8	6.8	6.8

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1
2,5°	40.2	41.5	43.4	44.1	44.9	44.9	29.3	28.7	28.5	28.2	28.5	28.5	27.9
5,0°	65.8	70.3	71.6	70.0	71.3	73.7	47.3	40.0	36.0	35.8	29.8	27.9	29.3
7,5°	99.5	106.0	107.3	110.7	112.3	116.0	50.7	50.1	54.8	53.5	52.5	44.4	38.7
10,0°	151.7	157.8	168.7	176.6	182.0	178.1	80.2	62.2	51.7	48.6	46.0	48.6	50.7
12,5°	182.3	178.1	184.7	186.7	188.6	183.9	97.7	97.4	95.3	90.4	73.4	65.0	45.2
15,0°	203.7	213.9	225.7	237.9	247.3	252.3	90.9	85.1	85.1	100.6	95.6	89.1	74.7
17,5°	226.4	242.9	257.8	275.8	287.6	287.8	121.2	133.7	112.3	107.1	97.7	91.7	99.8
20,0°	224.4	237.9	256.5	264.0	267.7	269.0	132.9	124.3	108.4	100.0	91.9	88.0	81.0
22,5°	241.3	245.8	259.3	268.2	273.2	273.7	149.4	145.2	128.5	108.9	86.4	81.0	63.2
25,0°	252.0	259.3	273.2	277.4	274.2	272.7	135.3	126.9	133.7	124.3	101.3	84.1	59.3
27,5°	271.4	272.9	275.0	281.8	284.4	283.1	161.7	129.8	124.1	112.8	98.7	79.7	58.0
30,0°	299.0	305.1	297.0	296.2	291.0	283.1	183.6	157.5	135.8	113.1	97.4	71.0	47.8
32,5°	329.3	325.9	307.9	310.3	317.6	317.6	161.7	147.3	130.3	106.6	91.7	56.9	36.6
35,0°	341.9	350.8	337.4	330.9	335.1	336.9	204.2	160.6	131.6	112.0	86.7	49.1	33.2
37,5°	364.3	367.2	344.5	340.6	350.5	353.6	221.5	171.1	138.4	121.7	79.4	42.0	38.1
40,0°	375.8	373.5	347.4	351.0	364.1	371.9	224.9	178.6	148.1	124.3	67.6	41.0	37.9
42,5°	393.6	370.3	352.3	357.6	369.8	379.2	245.5	183.9	155.9	118.1	57.5	43.1	40.0
45,0°	408.0	367.7	356.8	366.7	377.4	382.9	272.9	198.2	156.2	107.3	50.4	46.2	42.3
47,5°	413.2	363.6	357.3	369.3	379.8	381.8	279.2	199.3	158.8	89.1	47.0	45.7	41.5
50,0°	402.2	356.5	351.5	360.2	374.3	377.7	277.9	196.7	154.4	66.3	44.4	42.8	37.3
52,5°	377.4	338.0	339.5	349.2	367.0	369.8	278.9	200.1	150.2	52.0	40.0	37.9	33.4
55,0°	342.4	311.3	309.5	324.4	351.8	359.4	280.5	193.5	132.2	40.7	35.8	33.2	30.0
57,5°	313.2	274.8	269.3	290.7	319.7	326.5	269.5	170.3	94.0	42.3	32.4	30.6	27.4
60,0°	282.1	237.9	219.6	243.4	277.4	287.3	217.8	145.5	62.7	41.5	30.6	27.7	26.1
62,5°	230.1	186.7	175.2	188.0	209.2	225.7	169.0	109.4	48.3	37.6	29.0	26.6	25.6
65,0°	183.1	136.9	131.1	136.1	146.3	144.7	125.4	81.2	47.8	38.1	31.6	29.5	26.9
67,5°	145.5	93.5	79.9	81.7	85.4	84.6	113.4	69.5	60.6	47.8	37.3	32.9	29.5
70,0°	119.4	74.4	47.5	43.9	42.8	45.4	120.7	76.0	69.2	48.1	41.3	35.8	32.1
72,5°	85.1	61.9	31.9	24.0	23.0	23.5	115.2	78.6	66.9	44.1	42.6	35.5	33.4
75,0°	67.6	31.1	23.0	18.5	17.8	17.8	69.7	65.6	57.2	44.4	45.7	37.3	35.0
77,5°	46.0	21.7	17.5	15.9	15.9	15.7	64.8	52.5	47.3	43.4	40.5	38.7	37.1
80,0°	18.0	15.4	14.9	14.6	14.6	14.6	52.2	48.8	47.0	43.4	37.6	39.4	30.3
82,5°	14.9	13.8	13.6	13.6	13.6	13.6	37.1	38.7	40.5	37.6	35.5	26.9	17.0
85,0°	13.8	13.3	12.8	12.8	13.1	13.1	20.1	24.0	30.3	34.0	23.5	17.5	14.1
87,5°	12.0	11.8	11.8	12.0	12.0	12.0	12.0	12.5	12.0	9.4	8.9	8.4	7.3
90,0°	11.0	11.0	11.2	11.2	11.2	11.0	10.2	9.4	8.9	8.4	7.8	7.3	6.8
92,5°	10.4	10.4	10.4	10.4	10.4	10.4	9.1	8.9	8.4	7.8	7.3	6.8	6.3
95,0°	9.7	9.7	9.7	9.7	9.7	9.9	8.6	8.4	7.8	7.6	7.1	6.8	6.3
97,5°	9.1	8.9	8.9	8.9	8.9	8.9	8.4	7.8	7.6	7.3	6.8	6.3	6.3
100,0°	8.6	8.4	8.4	8.4	8.4	8.4	7.8	7.6	7.3	6.8	6.8	6.3	6.0
102,5°	8.1	8.1	8.4	8.4	8.1	8.4	7.6	7.3	7.1	6.8	6.3	6.0	5.7
105,0°	7.8	7.8	7.8	7.8	7.8	7.8	7.3	6.8	6.8	6.3	6.0	5.7	5.5
107,5°	7.6	7.3	7.3	7.3	7.3	7.3	6.8	6.5	6.3	6.0	5.7	5.2	5.2
110,0°	7.3	7.3	7.3	7.3	7.3	6.3	6.3	6.3	6.0	5.7	5.2	5.2	5.0
112,5°	6.8	6.8	6.8	6.8	6.8	5.7	6.3	5.7	5.7	5.2	5.2	4.7	4.7

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	0.0	0.0
2,5°	27.7	27.9	28.5	28.2	27.7	27.7	27.7	29.0	29.8	29.8	29.8	0.4	0.5
5,0°	30.8	30.8	31.1	29.5	27.4	25.6	23.5	22.2	21.4	20.9	20.9	1.1	1.5
7,5°	32.6	37.6	39.7	37.3	35.5	31.3	25.6	21.7	19.3	18.3	18.3	2.3	3.8
10,0°	50.1	42.0	47.8	58.2	49.1	32.9	24.8	21.2	19.1	17.5	16.7	4.2	8.0
12,5°	44.9	47.5	51.5	54.6	42.0	27.4	20.4	17.5	17.8	18.3	17.8	6.1	14.1
15,0°	64.5	47.5	52.2	56.7	57.7	38.9	29.5	20.1	18.8	19.6	19.3	9.0	23.1
17,5°	86.4	68.4	55.9	45.4	29.0	30.6	37.3	31.6	23.8	19.1	16.2	11.5	34.6
20,0°	58.2	46.8	42.8	42.0	37.3	36.3	32.6	24.6	24.0	28.5	27.2	13.0	47.6
22,5°	45.4	35.0	32.6	30.8	31.3	30.0	29.8	25.6	28.2	30.8	28.2	14.9	62.5
25,0°	35.0	27.4	25.1	24.0	24.0	24.6	27.4	27.9	31.6	40.2	38.1	16.6	79.1
27,5°	37.1	27.9	23.2	20.6	20.4	19.8	25.9	28.5	24.6	29.0	29.8	19.1	98.2
30,0°	32.9	27.4	22.2	21.2	19.3	18.8	20.1	20.6	16.7	18.5	17.8	21.6	119.8
32,5°	31.6	27.9	23.0	21.2	19.3	17.2	17.5	17.5	14.4	15.9	15.7	24.3	144.1
35,0°	29.8	26.6	24.6	20.9	18.8	17.0	16.5	15.9	13.6	14.1	14.1	28.3	172.4
37,5°	32.1	26.4	22.2	20.1	19.3	17.0	15.7	14.9	13.3	13.3	13.6	31.7	204.2
40,0°	33.2	29.0	22.5	19.6	17.8	16.2	15.4	14.9	13.6	13.3	13.1	35.1	239.2
42,5°	34.7	27.9	23.2	21.7	17.8	16.2	14.9	14.4	13.1	12.8	13.1	38.5	277.7
45,0°	35.8	28.2	23.0	20.1	18.5	17.5	15.7	14.4	13.1	12.3	12.5	42.2	320.0
47,5°	35.0	28.5	23.2	23.2	22.7	21.2	18.3	15.9	13.8	12.3	12.0	46.1	366.1
50,0°	31.9	26.1	23.0	26.4	29.5	27.9	26.4	23.8	20.6	19.1	18.8	49.8	415.9
52,5°	28.5	24.6	24.0	30.3	34.7	35.3	34.0	32.4	31.1	29.0	28.2	53.1	469.1
55,0°	26.1	23.8	24.6	31.6	37.6	39.2	39.4	36.8	36.0	36.8	36.0	55.8	524.9
57,5°	24.6	23.2	24.3	31.1	36.6	40.0	41.8	39.7	38.1	37.1	36.6	57.6	582.5
60,0°	23.2	21.7	23.5	30.0	35.5	39.7	40.7	38.9	37.1	36.3	36.0	57.0	639.4
62,5°	22.7	21.4	24.6	29.5	34.7	38.7	40.0	38.4	35.0	35.0	34.5	54.9	694.3
65,0°	24.6	23.5	25.9	28.7	32.6	35.3	36.8	35.5	32.6	32.9	32.4	51.8	746.2
67,5°	28.5	26.9	27.2	30.0	32.4	33.2	33.2	30.6	27.9	26.4	26.1	48.7	794.8
70,0°	33.4	30.6	30.0	30.3	29.8	28.2	27.2	26.1	25.3	24.8	24.0	46.6	841.4
72,5°	34.5	32.6	30.6	31.1	27.7	22.5	21.4	20.6	20.4	19.8	19.8	42.5	883.9
75,0°	34.5	36.0	32.6	29.8	20.6	17.5	17.0	16.5	16.7	16.2	16.2	35.3	919.2
77,5°	34.5	27.4	14.9	13.3	12.5	11.5	11.0	11.0	11.8	11.2	12.0	24.2	943.4
80,0°	19.6	11.0	9.1	9.4	8.6	8.4	7.8	8.1	7.6	6.3	6.8	13.8	957.2
82,5°	13.6	10.4	7.8	7.1	6.5	6.3	6.3	5.7	4.7	4.2	4.2	8.4	965.6
85,0°	11.0	8.4	6.8	6.0	5.5	5.2	4.7	4.2	4.2	3.7	3.7	4.8	970.4
87,5°	6.8	6.3	5.7	5.2	5.0	4.7	4.2	3.7	3.7	3.7	3.7	2.7	973.1
90,0°	6.3	5.7	5.2	5.0	4.7	4.2	3.7	3.7	3.1	3.1	3.1	2.4	975.5
92,5°	6.0	5.5	5.2	4.7	4.2	4.2	3.7	3.4	3.1	3.1	3.1	2.2	977.8
95,0°	5.7	5.2	5.2	4.7	4.2	4.2	3.7	3.4	3.1	3.1	3.1	2.1	979.9
97,5°	5.7	5.2	5.0	4.7	4.2	3.9	3.7	3.1	3.1	3.1	3.1	2.0	981.8
100,0°	5.7	5.2	5.0	4.7	4.2	3.9	3.7	3.4	3.1	3.1	3.1	1.9	983.7
102,5°	5.5	5.2	4.7	4.7	4.2	3.7	3.7	3.1	3.1	3.1	3.1	1.8	985.5
105,0°	5.2	5.0	4.7	4.2	4.2	3.7	3.7	3.1	3.1	3.1	3.1	1.7	987.2
107,5°	4.7	4.7	4.4	4.2	4.2	3.7	3.7	3.1	3.1	3.1	2.6	1.6	988.8
110,0°	4.7	4.7	4.2	4.2	3.7	3.7	3.4	3.1	3.1	2.9	2.6	1.5	990.3
112,5°	4.4	4.2	4.2	3.9	3.7	3.4	3.1	3.1	2.9	2.6	2.1	1.4	991.7

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
115,0°	5.7	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.8	6.8	6.8
117,5°	5.7	5.7	5.7	5.7	5.7	5.7	6.0	6.3	6.3	6.3	6.3	6.3	6.3
120,0°	5.2	5.2	5.5	5.5	5.7	5.7	5.7	5.7	5.7	5.7	5.7	6.3	6.3
122,5°	4.7	5.0	5.2	5.2	5.2	5.2	5.2	5.2	5.5	5.7	5.7	5.7	5.7
125,0°	4.2	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	5.2	5.2	5.2	5.2
127,5°	3.7	3.7	3.7	3.7	3.9	3.9	4.2	4.2	4.2	4.2	4.2	4.2	4.2
130,0°	2.9	2.9	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
132,5°	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1
135,0°	2.1	2.1	2.1	2.1	1.8	2.1	1.8	1.8	1.8	1.8	1.6	1.6	1.6
137,5°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
140,0°	1.6	1.6	1.6	1.6	1.3	1.3	1.0	1.0	1.3	1.0	1.0	1.0	1.0
142,5°	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
145,0°	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.8	0.5	0.5
147,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
115,0°	6.8	6.8	6.8	6.8	6.0	3.1	5.7	5.7	5.2	5.2	4.7	4.7	4.4
117,5°	6.3	6.3	6.3	6.3	5.2	2.6	5.2	5.2	5.0	4.7	4.7	4.2	4.2
120,0°	6.3	6.3	6.3	6.3	4.7	2.1	5.2	4.7	4.7	4.7	4.2	4.2	4.2
122,5°	5.7	5.7	5.7	5.7	3.7	1.6	4.7	4.7	4.2	4.2	4.2	3.9	3.7
125,0°	5.2	5.2	5.2	5.2	3.4	1.6	4.2	4.2	4.2	3.7	3.7	3.7	3.7
127,5°	4.2	4.2	4.2	4.2	2.6	1.6	3.7	3.7	3.7	3.1	3.1	3.1	3.1
130,0°	3.1	3.1	3.1	3.1	2.1	1.0	2.9	2.6	2.6	2.6	2.6	2.6	2.6
132,5°	2.1	2.1	2.1	2.1	1.6	1.0	2.1	2.1	2.1	2.1	2.1	2.1	2.1
135,0°	1.8	1.6	1.6	1.6	1.0	1.0	2.1	2.1	1.8	2.1	1.8	1.6	1.8
137,5°	1.6	1.6	1.6	1.3	1.0	0.5	1.6	1.6	1.6	1.6	1.6	1.6	1.6
140,0°	1.0	1.0	1.0	1.0	0.5	0.5	1.6	1.6	1.6	1.6	1.6	1.6	1.6
142,5°	1.0	1.0	1.0	0.5	0.5	0.5	1.3	1.0	1.6	1.3	1.6	1.3	1.6
145,0°	0.5	0.5	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.0	1.0	1.0
147,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	4.2	4.2	3.9	3.7	3.7	3.4	3.1	3.1	2.6	2.4	1.6	1.3	993.0
117,5°	4.2	3.7	3.7	3.7	3.1	3.1	3.1	2.9	2.6	2.1	1.6	1.2	994.1
120,0°	3.7	3.7	3.7	3.1	3.1	3.1	2.6	2.6	2.6	2.1	1.6	1.1	995.3
122,5°	3.7	3.4	3.1	3.1	3.1	2.9	2.6	2.6	2.6	2.1	1.6	1.0	996.3
125,0°	3.4	3.1	3.1	3.1	2.6	2.6	2.6	2.6	2.1	1.8	1.6	0.9	997.2
127,5°	3.1	2.6	2.6	2.6	2.6	2.4	2.1	2.1	2.1	1.6	1.6	0.7	997.9
130,0°	2.6	2.1	2.1	2.1	2.1	2.1	2.1	1.6	1.6	1.6	1.6	0.6	998.4
132,5°	2.1	2.1	2.1	2.1	1.8	1.6	1.6	1.6	1.6	1.6	1.6	0.4	998.8
135,0°	1.8	1.8	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.3	999.2
137,5°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.0	1.0	0.3	999.4
140,0°	1.6	1.6	1.6	1.6	1.6	1.6	1.3	1.0	1.0	1.0	1.0	0.2	999.7
142,5°	1.6	1.3	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.2	999.9
145,0°	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.1	1000.0
147,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235MF14H + 5XA54000XBS EAN: 4058352833247 + 4050737971445	LP number 59054_23
Dimming levels table		environmental temperature: 25°C
siteco		

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption	Power consumption	Power consumption
				[W] start of lifetime	[W] end of lifetime	[W] average
100	254	254	1540	11.8	12.1	12.0
95	241	252	1461	11.1	11.4	11.2
90	229	250	1388	10.6	10.8	10.7
85	216	248	1310	9.9	10.2	10.0
80	203	246	1231	9.3	9.6	9.4
75	190	243	1152	8.7	9.0	8.8
70	178	241	1079	8.2	8.4	8.3
65	165	238	1000	7.6	7.7	7.6
60	152	235	922	7.0	7.2	7.1
55	140	232	849	6.5	6.6	6.6
50	127	229	770	6.0	6.1	6.0
45	114	225	691	5.4	5.6	5.5
40	102	221	618	5.0	5.1	5.0
35	89	216	540	4.5	4.6	4.6
30	76	210	461	4.0	4.0	4.0
26	65	204	394	3.6	3.7	3.6