




Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1ECN4CXS EAN: 4058352890103	LP number 59263_124
	Version cover frosted, elliptical narrow distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-Multilumen CLOi Rated values Net luminous flux = 12350 lm Power consumption = 68.4 W Luminous efficacy = 180.6 lm/W	serial documentation 17.08.2023
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 1670 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=85 N2=95 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1ECN4CXS EAN: 4058352890103	LP number 59263_124
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	10.0	10.0
5°	1493.3	1495.6	1516.6	1565.9	1616.3	1649.8	1662.9	75.0	85.0
10°	1088.5	1106.7	1175.0	1303.4	1460.6	1586.1	1636.2	126.8	211.8
15°	678.3	712.7	825.0	1006.5	1239.9	1474.8	1578.7	151.0	362.9
20°	362.1	388.9	492.0	707.6	980.6	1275.8	1432.9	148.2	511.0
25°	217.8	231.1	285.8	436.7	705.9	972.9	1137.5	127.8	638.8
30°	151.3	158.5	185.3	264.1	455.8	646.3	761.7	99.0	737.8
35°	95.4	107.0	131.3	171.8	268.4	391.1	463.8	70.7	808.5
40°	57.7	64.5	93.9	120.6	157.9	239.7	291.4	50.0	858.5
45°	43.5	45.9	58.2	86.3	99.5	145.4	176.9	35.2	893.7
50°	37.7	39.0	42.8	61.0	68.3	89.3	109.1	26.2	919.9
55°	34.6	35.0	36.7	43.5	50.5	59.6	73.7	20.9	940.8
60°	30.2	31.1	32.8	34.2	38.6	42.0	53.5	17.5	958.3
65°	23.9	25.4	29.1	28.1	30.1	30.8	41.3	14.6	972.8
70°	17.0	18.4	22.5	23.3	23.4	22.7	30.8	11.5	984.3
75°	10.9	12.0	16.2	17.9	17.4	15.7	20.7	8.4	992.7
80°	6.2	6.7	9.0	10.7	11.0	9.3	11.6	5.0	997.7
85°	3.1	3.3	4.2	5.0	4.8	3.9	4.2	2.3	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1ECN4CXS EAN: 4058352890103	LP number 59263_124
---------------------------------------	----------------------------------------------------------------	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.9	17.1	16.2	17.4	17.7	20.9	22.1	21.2	22.4	22.8
	3H	17.1	18.1	17.4	18.5	18.8	21.5	22.5	21.9	22.9	23.2
	4H	17.4	18.5	17.8	18.8	19.2	21.7	22.7	22.1	23.1	23.4
	6H	17.6	18.6	18.0	19.0	19.4	22.0	22.8	22.4	23.2	23.6
	8H	17.8	18.6	18.3	19.0	19.4	22.1	22.9	22.5	23.2	23.6
	12H	17.9	18.6	18.3	19.0	19.5	22.1	22.8	22.6	23.2	23.6
4H	2H	16.7	17.7	17.1	18.0	18.4	20.9	21.9	21.3	22.3	22.6
	3H	18.1	19.0	18.6	19.3	19.8	21.6	22.4	22.0	22.8	23.2
	4H	18.6	19.4	19.1	19.8	20.2	22.0	22.7	22.4	23.1	23.6
	6H	18.9	19.6	19.4	20.0	20.5	22.3	22.9	22.7	23.3	23.8
	8H	19.0	19.6	19.5	20.1	20.6	22.4	22.9	22.9	23.4	23.9
	12H	19.1	19.6	19.6	20.1	20.6	22.5	22.9	22.9	23.4	23.9
8H	4H	19.1	19.7	19.6	20.1	20.6	22.1	22.6	22.5	23.1	23.6
	6H	19.6	20.0	20.1	20.5	21.0	22.5	22.9	23.0	23.4	23.9
	8H	19.7	20.1	20.2	20.6	21.1	22.6	23.0	23.1	23.5	24.0
	12H	19.8	20.2	20.4	20.7	21.2	22.7	23.0	23.2	23.5	24.1
12H	4H	19.2	19.6	19.7	20.1	20.6	22.0	22.6	22.5	23.0	23.5
	6H	19.7	20.0	20.2	20.5	21.1	22.5	22.9	23.0	23.4	23.9
	8H	19.9	20.2	20.4	20.7	21.3	22.6	23.0	23.1	23.5	24.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500
			B = 58


C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		8730.6	9209.6	11674.2	17320.6	19981.8	29189.5	35521.3	
50°		8334.3	8608.4	9451.3	13479.0	15085.9	19727.7	24101.7	
55°		8553.7	8657.4	9087.8	10759.6	12502.4	14756.8	18244.7	
60°		8561.5	8842.9	9316.4	9717.3	10956.9	11918.7	15186.8	
65°		8037.2	8522.9	9780.2	9441.6	10120.4	10338.4	13877.0	
70°		7046.2	7621.5	9329.8	9679.7	9710.4	9407.8	12795.0	
75°		5954.7	6586.6	8881.9	9835.7	9551.6	8633.4	11347.3	
80°		5030.8	5440.3	7362.2	8711.9	8967.8	7592.8	9499.1	
85°		5089.8	5428.6	6907.5	8187.7	7844.0	6342.3	6796.7	

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1ECN4CXS EAN: 4058352890103	LP number 59263_124
---------------------------------------	----------------------------------------------------------------	--------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1ECN4CXS EAN: 4058352890103	LP number 59263_124
---------------------------------------	----------------------------------------------------------------	--------------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption	Power consumption
	1	2	3			end of lifetime [W]	average [W]
1	A	C	E	12350	68.4	83.1	75.8
2	A	C	F	11846	65.4	79.7	72.6
3	A	D	E	10838	59.4	71.9	65.6
4	A	D	F	9882	53.9	64.9	59.4
5	B	C	E	8853	47.9	57.7	52.8
6	B	C	F	7866	42.4	50.9	46.6
7	B	D	E	6879	37.1	44.2	40.7
8	B	D	F	5881	31.6	37.5	34.6