




Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EMN4A5G EAN: 4058352891902	LP number 59263_177
	Version cover frosted, elliptical narrow distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Multilumen Rated values Net luminous flux = 10630 lm Power consumption = 60.5 W Luminous efficacy = 175.7 lm/W	serial documentation 24.08.2023
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 1670 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=85 N2=95 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EMN4A5G EAN: 4058352891902	LP number 59263_177
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	10.0	10.0
5°	1493.3	1495.6	1516.6	1565.9	1616.3	1649.8	1662.9	75.0	85.0
10°	1088.5	1106.7	1175.0	1303.4	1460.6	1586.1	1636.2	126.8	211.8
15°	678.3	712.7	825.0	1006.5	1239.9	1474.8	1578.7	151.0	362.9
20°	362.1	388.9	492.0	707.6	980.6	1275.8	1432.9	148.2	511.0
25°	217.8	231.1	285.8	436.7	705.9	972.9	1137.5	127.8	638.8
30°	151.3	158.5	185.3	264.1	455.8	646.3	761.7	99.0	737.8
35°	95.4	107.0	131.3	171.8	268.4	391.1	463.8	70.7	808.5
40°	57.7	64.5	93.9	120.6	157.9	239.7	291.4	50.0	858.5
45°	43.5	45.9	58.2	86.3	99.5	145.4	176.9	35.2	893.7
50°	37.7	39.0	42.8	61.0	68.3	89.3	109.1	26.2	919.9
55°	34.6	35.0	36.7	43.5	50.5	59.6	73.7	20.9	940.8
60°	30.2	31.1	32.8	34.2	38.6	42.0	53.5	17.5	958.3
65°	23.9	25.4	29.1	28.1	30.1	30.8	41.3	14.6	972.8
70°	17.0	18.4	22.5	23.3	23.4	22.7	30.8	11.5	984.3
75°	10.9	12.0	16.2	17.9	17.4	15.7	20.7	8.4	992.7
80°	6.2	6.7	9.0	10.7	11.0	9.3	11.6	5.0	997.7
85°	3.1	3.3	4.2	5.0	4.8	3.9	4.2	2.3	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EMN4A5G EAN: 4058352891902	LP number 59263_177
---------------------------------------	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.4	16.6	15.7	16.9	17.2	20.4	21.6	20.7	21.9	22.2
	3H	16.5	17.6	16.9	18.0	18.3	21.0	22.0	21.3	22.3	22.7
	4H	16.9	17.9	17.3	18.3	18.7	21.2	22.2	21.6	22.5	22.9
	6H	17.1	18.1	17.5	18.4	18.8	21.5	22.3	21.9	22.7	23.1
	8H	17.3	18.1	17.7	18.5	18.9	21.6	22.3	22.0	22.7	23.1
	12H	17.3	18.1	17.8	18.5	18.9	21.6	22.3	22.1	22.7	23.1
4H	2H	16.2	17.1	16.6	17.5	17.9	20.4	21.4	20.7	21.7	22.1
	3H	17.6	18.4	18.0	18.8	19.2	21.1	21.9	21.5	22.3	22.7
	4H	18.1	18.9	18.6	19.3	19.7	21.4	22.2	21.9	22.6	23.0
	6H	18.4	19.1	18.9	19.5	20.0	21.7	22.4	22.2	22.8	23.3
	8H	18.5	19.1	19.0	19.6	20.0	21.9	22.4	22.4	22.9	23.3
	12H	18.6	19.1	19.1	19.6	20.1	21.9	22.4	22.4	22.9	23.4
8H	4H	18.6	19.1	19.1	19.6	20.1	21.5	22.1	22.0	22.6	23.0
	6H	19.1	19.5	19.6	20.0	20.5	22.0	22.4	22.4	22.9	23.4
	8H	19.2	19.6	19.7	20.1	20.6	22.1	22.5	22.6	23.0	23.5
	12H	19.3	19.7	19.8	20.2	20.7	22.2	22.5	22.7	23.0	23.6
12H	4H	18.6	19.1	19.1	19.6	20.1	21.5	22.0	22.0	22.5	23.0
	6H	19.1	19.5	19.7	20.0	20.5	21.9	22.3	22.4	22.8	23.4
	8H	19.3	19.7	19.9	20.2	20.7	22.1	22.5	22.6	23.0	23.5

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500
			B = 58

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		7514.6	7926.9	10048.3	14908.3	17198.9	25124.3	30574.2	
50°		7173.6	7409.5	8135.0	11601.8	12984.9	16980.2	20745.1	
55°		7362.4	7451.7	7822.1	9261.1	10761.2	12701.6	15703.7	
60°		7369.2	7611.3	8018.9	8364.0	9430.9	10258.8	13071.7	
65°		6917.9	7335.9	8418.1	8126.6	8710.9	8898.6	11944.4	
70°		6064.9	6560.0	8030.4	8331.6	8358.0	8097.6	11013.1	
75°		5125.4	5669.2	7644.9	8465.9	8221.3	7431.0	9766.9	
80°		4330.1	4682.7	6336.9	7498.6	7718.8	6535.3	8176.2	
85°		4380.9	4672.5	5945.5	7047.4	6751.6	5459.0	5850.1	


Photometric test report

Family
Licross® 21 Recessed

Order number: 52TL1EMN4A5G
EAN: 4058352891902

LP number
59263_177

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EMN4A5G EAN: 4058352891902	LP number 59263_177
---------------------------------------	--	--------------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	10630	60.5
2	A	C	F	10010	56.5
3	A	D	E	9527	53.4
4	A	D	F	9033	50.3
5	B	C	E	8529	47.3
6	B	C	F	8025	44.4
7	B	D	E	7521	41.4
8	B	D	F	6996	38.4