

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TE1ECN4CXS
EAN: 4058352929360

LP number
59263_250



Version cover frosted, elliptical narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 12420 lm
 Power consumption = 66.5 W
 Luminous efficacy = 186.8 lm/W

serial
documentation
12.10.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 1670 cd/klm



Classifications

DIN 5040 A 7 0
 CIE N1=85 N2=95 N3=99
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE1ECN4CXS EAN: 4058352929360	LP number 59263_250
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	10.0	10.0
5°	1493.3	1495.6	1516.6	1565.9	1616.3	1649.8	1662.9	75.0	85.0
10°	1088.5	1106.7	1175.0	1303.4	1460.6	1586.1	1636.2	126.8	211.8
15°	678.3	712.7	825.0	1006.5	1239.9	1474.8	1578.7	151.0	362.9
20°	362.1	388.9	492.0	707.6	980.6	1275.8	1432.9	148.2	511.0
25°	217.8	231.1	285.8	436.7	705.9	972.9	1137.5	127.8	638.8
30°	151.3	158.5	185.3	264.1	455.8	646.3	761.7	99.0	737.8
35°	95.4	107.0	131.3	171.8	268.4	391.1	463.8	70.7	808.5
40°	57.7	64.5	93.9	120.6	157.9	239.7	291.4	50.0	858.5
45°	43.5	45.9	58.2	86.3	99.5	145.4	176.9	35.2	893.7
50°	37.7	39.0	42.8	61.0	68.3	89.3	109.1	26.2	919.9
55°	34.6	35.0	36.7	43.5	50.5	59.6	73.7	20.9	940.8
60°	30.2	31.1	32.8	34.2	38.6	42.0	53.5	17.5	958.3
65°	23.9	25.4	29.1	28.1	30.1	30.8	41.3	14.6	972.8
70°	17.0	18.4	22.5	23.3	23.4	22.7	30.8	11.5	984.3
75°	10.9	12.0	16.2	17.9	17.4	15.7	20.7	8.4	992.7
80°	6.2	6.7	9.0	10.7	11.0	9.3	11.6	5.0	997.7
85°	3.1	3.3	4.2	5.0	4.8	3.9	4.2	2.3	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE1ECN4CXS EAN: 4058352929360	LP number 59263_250
--------------------------------	--	------------------------

UGR-Table		Standard room									siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimensions		View crosswise (C0)					View endwise (C90)					
x	y											
2H	2H	15.9	17.1	16.3	17.4	17.8	20.9	22.1	21.3	22.5	22.8	
	3H	17.1	18.2	17.5	18.5	18.9	21.5	22.5	21.9	22.9	23.2	
	4H	17.4	18.5	17.8	18.8	19.2	21.8	22.7	22.2	23.1	23.5	
	6H	17.7	18.6	18.1	19.0	19.4	22.0	22.8	22.4	23.2	23.6	
	8H	17.9	18.7	18.3	19.0	19.5	22.1	22.9	22.6	23.3	23.7	
	12H	17.9	18.7	18.3	19.1	19.5	22.2	22.8	22.6	23.2	23.7	
4H	2H	16.7	17.7	17.1	18.0	18.4	20.9	21.9	21.3	22.3	22.7	
	3H	18.2	19.0	18.6	19.4	19.8	21.6	22.5	22.0	22.8	23.3	
	4H	18.7	19.4	19.1	19.8	20.3	22.0	22.7	22.4	23.1	23.6	
	6H	18.9	19.6	19.4	20.0	20.5	22.3	22.9	22.7	23.3	23.8	
	8H	19.1	19.6	19.5	20.1	20.6	22.4	22.9	22.9	23.4	23.9	
	12H	19.2	19.7	19.6	20.1	20.6	22.5	22.9	23.0	23.4	23.9	
8H	4H	19.1	19.7	19.6	20.1	20.6	22.1	22.7	22.6	23.1	23.6	
	6H	19.6	20.0	20.1	20.5	21.0	22.5	22.9	23.0	23.4	23.9	
	8H	19.7	20.1	20.2	20.6	21.2	22.6	23.0	23.1	23.5	24.0	
	12H	19.8	20.2	20.4	20.7	21.3	22.7	23.0	23.2	23.5	24.1	
12H	4H	19.2	19.6	19.7	20.1	20.6	22.1	22.6	22.6	23.0	23.5	
	6H	19.7	20.1	20.2	20.6	21.1	22.5	22.9	23.0	23.4	23.9	
	8H	19.9	20.2	20.4	20.7	21.3	22.6	23.0	23.2	23.5	24.0	

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	8780.0	9261.8	11740.4	17418.8	20095.0	29355.0	35722.6
50°	8381.6	8657.2	9504.9	13555.4	15171.4	19839.6	24238.3
55°	8602.2	8706.5	9139.3	10820.6	12573.3	14840.4	18348.1
60°	8610.1	8893.0	9369.2	9772.4	11019.0	11986.3	15272.9
65°	8082.8	8571.2	9835.6	9495.1	10177.8	10397.0	13955.7
70°	7086.2	7664.7	9382.7	9734.6	9765.5	9461.2	12867.6
75°	5988.5	6623.9	8932.2	9891.4	9605.7	8682.4	11411.6
80°	5059.3	5471.2	7404.0	8761.3	9018.6	7635.8	9553.0
85°	5118.7	5459.4	6946.6	8234.1	7888.5	6378.3	6835.3

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TE1ECN4CXS
EAN: 4058352929360

LP number
59263_250

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 11 Recessed	Order number: 51TE1ECN4CXS EAN: 4058352929360	LP number 59263_250
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	12420	66.5	74.5	70.5
2	A	C	F	11820	63.0	70.9	67.0
3	A	D	E	10840	57.4	64.3	60.8
4	A	D	F	9860	51.7	57.8	54.8
5	B	C	E	8860	46.2	51.3	48.8
6	B	C	F	7920	41.1	45.8	43.4
7	B	D	E	6900	35.6	39.4	37.5
8	B	D	F	5950	30.7	34.0	32.4