

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TL12MN4AXG
EAN: 4058352922460

LP number
58637_201



Version cover frosted, wide distribution, high visual comfort
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG Multilumen
Rated values Net luminous flux = 10290 lm
Power consumption = 55.2 W
Luminous efficacy = 186.4 lm/W

serial
documentation
11.10.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 498 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=67 N2=92 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12MN4AXG EAN: 4058352922460	LP number 58637_201
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	482.3	482.3	482.3	482.3	482.3	482.3	482.3	2.9	2.9
5°	485.4	482.8	478.2	477.5	477.4	475.9	475.7	22.9	25.8
10°	492.7	488.2	477.9	471.3	467.6	465.9	466.0	45.2	71.0
15°	493.2	486.1	471.9	467.9	471.0	473.7	476.3	67.5	138.5
20°	482.5	473.5	462.5	471.9	487.1	492.8	494.9	89.9	228.4
25°	456.4	447.1	449.2	479.4	497.6	491.1	485.8	109.5	337.8
30°	414.9	406.8	427.0	475.1	479.0	447.1	431.1	121.4	459.2
35°	364.2	358.0	387.7	436.7	420.7	368.9	346.8	122.0	581.2
40°	300.5	296.3	322.5	357.9	336.0	284.8	262.9	110.4	691.6
45°	229.2	226.3	238.5	259.8	247.2	211.8	193.4	90.1	781.7
50°	162.3	159.3	161.6	173.6	174.5	155.2	138.5	68.2	849.9
55°	112.5	108.0	105.1	112.3	121.6	110.9	97.2	49.6	899.5
60°	78.7	73.1	68.3	73.1	83.7	77.4	68.5	35.5	935.0
65°	56.0	50.2	45.0	48.4	56.8	54.5	49.6	25.5	960.5
70°	39.5	34.5	29.5	32.1	37.8	38.5	36.6	18.1	978.6
75°	26.0	22.0	18.4	20.2	23.9	25.9	25.8	12.0	990.6
80°	14.9	12.2	9.9	10.8	13.0	14.8	15.3	6.8	997.4
85°	5.4	4.3	3.6	4.0	4.7	5.6	5.8	2.5	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12MN4AXG EAN: 4058352922460	LP number 58637_201
--------------------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	22.7	24.2	23.1	24.5	24.8	22.8	24.3	23.2	24.6	24.9
	3H	23.2	24.6	23.6	24.9	25.3	23.4	24.7	23.7	25.0	25.4
	4H	23.5	24.7	23.9	25.1	25.4	23.6	24.8	24.0	25.2	25.6
	6H	23.6	24.8	24.0	25.1	25.5	23.8	24.9	24.2	25.3	25.7
	8H	23.7	24.8	24.2	25.1	25.6	23.9	24.9	24.3	25.3	25.7
	12H	23.8	24.7	24.2	25.1	25.5	23.9	24.9	24.4	25.3	25.7
4H	2H	22.9	24.2	23.3	24.5	24.9	23.0	24.3	23.4	24.6	25.0
	3H	23.6	24.6	24.0	25.0	25.4	23.8	24.8	24.2	25.2	25.6
	4H	23.8	24.8	24.3	25.2	25.6	24.1	25.0	24.5	25.4	25.8
	6H	24.1	24.9	24.5	25.3	25.7	24.4	25.2	24.8	25.6	26.1
	8H	24.1	24.9	24.6	25.3	25.8	24.5	25.2	24.9	25.6	26.1
	12H	24.2	24.8	24.7	25.3	25.8	24.5	25.2	25.0	25.6	26.1
8H	4H	23.9	24.6	24.4	25.1	25.5	24.1	24.9	24.6	25.3	25.8
	6H	24.2	24.7	24.7	25.2	25.7	24.5	25.1	25.0	25.5	26.0
	8H	24.3	24.8	24.8	25.3	25.8	24.6	25.1	25.1	25.6	26.1
	12H	24.3	24.8	24.8	25.3	25.8	24.7	25.1	25.2	25.6	26.2
12H	4H	23.9	24.5	24.4	25.0	25.5	24.1	24.8	24.6	25.2	25.7
	6H	24.2	24.7	24.7	25.2	25.7	24.5	25.0	25.0	25.5	26.0
	8H	24.3	24.7	24.8	25.2	25.8	24.6	25.1	25.1	25.6	26.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	38329.8	37853.4	39894.6	43453.9	41342.6	35433.9	32341.6
50°	29864.1	29319.3	29735.5	31950.2	32114.7	28564.0	25486.1
55°	23194.7	22267.5	21674.5	23166.0	25083.5	22877.9	20039.1
60°	18619.0	17301.6	16162.2	17299.7	19788.7	18301.1	16192.0
65°	15681.9	14037.7	12602.0	13555.5	15898.5	15252.3	13892.5
70°	13654.9	11924.4	10207.4	11099.6	13065.9	13319.8	12667.9
75°	11865.6	10064.6	8423.6	9228.8	10907.3	11847.7	11783.8
80°	10122.9	8294.7	6729.5	7368.4	8823.3	10109.2	10434.8
85°	7260.3	5873.4	4866.4	5407.9	6401.3	7552.1	7866.9

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TL12MN4AXG
EAN: 4058352922460

LP number
58637_201

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12MN4AXG EAN: 4058352922460	LP number 58637_201
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	10290	55.2
2	A	C	F	9840	52.5
3	A	D	E	9310	49.3
4	A	D	F	8780	46.2
5	B	C	E	8010	41.7
6	B	C	F	7770	40.4
7	B	D	E	7220	37.4
8	B	D	F	6750	34.8