


Photometric test report

Family Lunis 21	Order number: 51DB17ED91C EAN: 4069025013187	LP number 59679_5
	Version	recessed luminaire, Combined lens and reflector optics, reflector, black, rotationally symmetrical wide distribution, adjustable color temperature: 3000K 4000K 6500K, UGR≤19 (L65≤1000cd/m²)
	Lamps	LED 4000 K CRI ≥ 80
	Controlgear	ECG Multilumen
	Setting	factory setting: DIP-Step=5, colour temperature 4000K
	Rated values	Net luminous flux = 1790 lm Power consumption = 12.2 W Luminous efficacy = 146.7 lm/W
		serial documentation 27.09.2024
		siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 7 0	η_{LB}	100.0%
CIE	N1=93 N2=100 N3=100	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 21	Order number: 51DB17ED91C EAN: 4069025013187	LP number 59679_5
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	1152.7	0.3	0.3
1°	1149.6	2.2	2.5
2°	1144.3	4.4	6.9
3°	1138.0	6.5	13.4
4°	1130.6	8.6	22.0
5°	1121.1	10.7	32.8
6°	1111.6	12.7	45.5
7°	1100.1	14.7	60.2
8°	1087.4	16.6	76.8
9°	1073.7	18.4	95.2
10°	1060.0	20.2	115.4
11°	1044.0	21.8	137.2
12°	1027.3	23.4	160.7
13°	1009.8	24.9	185.6
14°	991.5	26.3	211.9
15°	972.2	27.6	239.5
16°	952.2	28.8	268.3
17°	930.8	29.8	298.1
18°	908.5	30.8	328.9
19°	885.4	31.6	360.5
20°	861.7	32.3	392.8
21°	836.8	32.9	425.7
22°	811.3	33.3	459.0
23°	784.8	33.6	492.7
24°	756.8	33.8	526.4
25°	726.6	33.7	560.1
26°	694.1	33.4	593.5
27°	658.0	32.8	626.2
28°	619.0	31.9	658.1
29°	578.6	30.8	688.8
30°	537.2	29.5	718.3
31°	498.6	28.2	746.5
32°	460.9	26.8	773.2
33°	423.0	25.3	798.5
34°	383.8	23.5	822.0
35°	342.3	21.5	843.6
36°	301.8	19.5	863.0
37°	267.7	17.7	880.7
38°	235.7	15.9	896.6
39°	204.6	14.1	910.7
40°	174.7	12.3	923.0
41°	146.5	10.5	933.6
42°	125.1	9.2	942.8
43°	106.6	8.0	950.7
44°	91.0	6.9	957.7
45°	75.3	5.8	963.5
46°	63.0	5.0	968.5

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	53.9	4.3	972.8
48°	46.1	3.8	976.5
49°	39.0	3.2	979.8
50°	33.0	2.8	982.5
51°	28.6	2.4	985.0
52°	24.6	2.1	987.1
53°	21.0	1.8	988.9
54°	18.3	1.6	990.6
55°	15.8	1.4	992.0
56°	13.5	1.2	993.2
57°	11.6	1.1	994.3
58°	9.8	0.9	995.2
59°	8.2	0.8	996.0
60°	6.6	0.6	996.6
61°	5.3	0.5	997.1
62°	4.1	0.4	997.5
63°	3.1	0.3	997.8
64°	2.2	0.2	998.0
65°	1.5	0.2	998.2
66°	1.1	0.1	998.3
67°	1.0	0.1	998.4
68°	0.9	0.1	998.5
69°	0.9	0.1	998.6
70°	0.9	0.1	998.7
71°	0.9	0.1	998.7
72°	0.8	0.1	998.8
73°	0.8	0.1	998.9
74°	0.8	0.1	999.0
75°	0.8	0.1	999.1
76°	0.7	0.1	999.2
77°	0.7	0.1	999.2
78°	0.7	0.1	999.3
79°	0.7	0.1	999.4
80°	0.7	0.1	999.5
81°	0.6	0.1	999.5
82°	0.6	0.1	999.6
83°	0.6	0.1	999.7
84°	0.6	0.1	999.7
85°	0.5	0.1	999.8
86°	0.5	0.1	999.8
87°	0.5	0.1	999.9
88°	0.5	0.1	999.9
89°	0.5	0.1	1000.0
90°	0.0	0.0	1000.0
180°	0.0	0.0	1000.0

Photometric test report

Family Lunis 21		Order number: 51DB17ED91C EAN: 4069025013187							LP number 59679_5	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
2H	x									
	y									
	2H	17.7	18.9	18.1	19.2	19.5	17.7	18.9	18.1	19.2
	3H	17.6	18.6	17.9	18.9	19.3	17.6	18.6	17.9	18.9
	4H	17.5	18.4	17.9	18.8	19.1	17.5	18.4	17.9	18.8
	6H	17.4	18.2	17.8	18.6	19.0	17.4	18.2	17.8	18.6
4H	8H	17.5	18.2	17.9	18.6	19.0	17.5	18.2	17.9	18.6
	12H	17.5	18.1	17.9	18.5	18.9	17.5	18.1	17.9	18.5
	2H	17.5	18.4	17.9	18.8	19.2	17.5	18.4	17.9	18.8
	3H	17.3	18.1	17.7	18.5	18.9	17.3	18.1	17.7	18.5
	4H	17.2	17.9	17.7	18.3	18.8	17.2	17.9	17.7	18.3
	6H	17.1	17.7	17.6	18.1	18.6	17.1	17.7	17.6	18.1
8H	8H	17.1	17.6	17.6	18.1	18.5	17.1	17.6	17.6	18.1
	12H	17.1	17.5	17.6	18.0	18.5	17.1	17.5	17.6	18.0
	4H	17.1	17.6	17.6	18.0	18.5	17.1	17.6	17.6	18.0
	6H	17.0	17.4	17.5	17.9	18.4	17.0	17.4	17.5	17.9
	8H	16.9	17.3	17.4	17.8	18.3	16.9	17.3	17.4	17.8
	12H	16.9	17.2	17.4	17.7	18.2	16.9	17.2	17.4	17.7
12H	4H	17.1	17.5	17.6	18.0	18.5	17.1	17.5	17.6	18.0
	6H	17.0	17.3	17.5	17.8	18.3	17.0	17.3	17.5	17.8
	8H	16.9	17.2	17.4	17.7	18.2	16.9	17.2	17.4	17.7
	2H	17.7	18.9	18.1	19.2	19.5	17.7	18.9	18.1	19.2
	3H	17.6	18.6	17.9	18.9	19.3	17.6	18.6	17.9	18.9
	4H	17.5	18.4	17.9	18.8	19.1	17.5	18.4	17.9	18.8

Luminance table		Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 135
C-planes	0°		
γ	Luminance in cd/m²		
45°	13316.4		
50°	6418.4		
55°	3445.9		
60°	1656.2		
65°	451.0		
70°	324.7		
75°	369.1		
80°	473.1		
85°	774.8		

Photometric test report

Family
Lunis 21

Order number: 51DB17ED91C
EAN: 4069025013187

LP number
59679_5

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family
Lunis 21

Order number: 51DB17ED91C
EAN: 4069025013187

LP number
59679_5

Multilumen Table

environmental temperature: 25°C

siteco

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
12	ON	ON	OFF	OFF	3470	25.4
11	ON	OFF	ON	ON	3100	21.7
10	ON	OFF	ON	OFF	2910	20.3
9	ON	OFF	OFF	ON	2770	19.2
8	ON	OFF	OFF	OFF	2580	17.7
7	OFF	ON	ON	ON	2260	15.5
6	OFF	ON	ON	OFF	2010	13.7
5	OFF	ON	OFF	ON	1790	12.2
4	OFF	ON	OFF	OFF	1530	10.5
3	OFF	OFF	ON	ON	1430	9.7
2	OFF	OFF	ON	OFF	1190	8.0
1	OFF	OFF	OFF	ON	910	6.1
0	OFF	OFF	OFF	OFF	670	4.4