

Photometric test report

Family
Highbay 21

Order number: 52HN12DB4QDA03
EAN: 4069025421845

LP number
59723_168

serial
documentation
20.03.2025

siteco



Version

primary light control with lens, PMMA, housing, white, wide distribution, with DALI multisensor

Lamps

LED 4000 K | CRI ≥ 80

Controlgear

ECG-DALI

Rated values

Net luminous flux = 38000 lm

Power consumption = 197.7 W


Luminous efficacy = 192.2 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 920 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=90 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN12DB4QDA03 EAN: 4069025421845	LP number 59723_168
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	791.0
2,5°	794.7	794.4	795.0	795.0	794.2	792.8	792.0
5,0°	809.1	811.4	809.6	807.9	804.8	800.8	797.1
7,5°	839.0	837.9	835.9	831.3	824.9	817.3	810.1
10,0°	873.0	873.9	866.7	857.6	846.5	834.6	825.0
12,5°	902.2	899.8	892.6	881.8	868.2	853.9	842.5
15,0°	912.4	911.0	905.2	895.6	883.1	869.5	858.7
17,5°	919.8	918.2	913.1	904.4	892.7	879.7	870.3
20,0°	913.1	910.4	906.8	900.7	891.6	880.0	870.9
22,5°	873.0	875.7	872.3	868.8	863.2	854.7	847.2
25,0°	810.1	803.4	805.6	804.0	800.6	794.9	789.9
27,5°	697.5	704.9	702.5	701.8	699.9	697.0	693.3
30,0°	593.2	587.4	585.8	584.9	582.5	580.2	578.9
32,5°	456.1	464.3	462.1	462.0	458.3	454.5	453.6
35,0°	347.7	343.4	342.9	343.5	340.5	335.4	333.2
37,5°	248.6	249.1	246.7	247.3	245.8	241.7	237.9
40,0°	174.7	169.8	171.0	172.0	172.0	169.5	166.1
42,5°	115.9	118.7	117.3	118.1	118.9	118.2	116.5
45,0°	82.2	79.8	80.4	81.1	81.3	81.6	80.9
47,5°	56.5	57.6	57.2	57.7	57.6	57.9	57.5
50,0°	42.4	41.3	41.7	42.1	42.1	42.1	42.0
52,5°	32.0	31.8	31.7	32.2	32.5	32.7	32.7
55,0°	25.6	24.9	25.0	25.6	26.1	26.6	26.9
57,5°	20.6	20.3	20.3	20.8	21.4	22.1	22.4
60,0°	17.2	16.8	16.6	17.2	18.2	18.6	18.9
62,5°	14.5	14.3	13.9	14.3	15.3	15.8	16.0
65,0°	13.1	12.5	12.0	12.2	13.0	13.5	13.7
67,5°	11.1	10.9	10.3	10.4	11.4	11.4	11.5
70,0°	9.4	9.0	8.7	8.7	9.6	9.3	9.5
72,5°	7.6	7.5	7.3	7.2	7.3	7.4	7.8
75,0°	5.9	5.7	5.6	5.7	5.6	5.7	6.1
77,5°	4.1	4.1	4.1	4.2	4.1	4.2	4.5
80,0°	2.6	2.5	2.5	2.7	2.7	2.8	2.9
82,5°	1.1	1.2	1.2	1.3	1.5	1.5	1.7
85,0°	0.5	0.5	0.5	0.5	0.5	0.5	0.6
87,5°	0.2	0.3	0.3	0.3	0.3	0.3	0.3

Photometric test report

Family Highbay 21	Order number: 52HN12DB4QDA03 EAN: 4069025421845	LP number 59723_168
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	1.2	1.2
2,5°	791.3	790.7	790.0	789.4	788.0	786.7	9.5	10.7
5,0°	794.2	790.9	788.1	786.0	783.2	781.9	19.1	29.7
7,5°	803.7	797.3	791.2	786.8	782.5	780.9	29.0	58.7
10,0°	816.7	808.7	801.4	796.1	791.2	788.9	39.5	98.2
12,5°	833.0	825.3	818.6	813.6	808.7	806.6	50.4	148.6
15,0°	850.7	844.9	836.9	832.9	831.6	829.0	61.4	210.0
17,5°	864.2	859.8	856.6	853.6	849.6	847.0	72.4	282.5
20,0°	864.8	860.1	856.9	853.9	850.4	848.0	82.3	364.7
22,5°	841.4	836.7	833.2	829.7	826.8	824.5	89.2	453.9
25,0°	786.0	782.5	779.1	775.6	772.9	771.0	91.6	545.4
27,5°	691.2	689.6	687.4	684.8	682.7	681.4	87.8	633.3
30,0°	578.6	579.1	578.3	576.4	575.3	574.3	79.6	712.9
32,5°	454.5	456.7	457.0	455.4	454.6	454.3	67.4	780.2
35,0°	335.0	337.7	338.0	336.6	336.0	336.2	53.3	833.5
37,5°	239.3	241.4	241.0	239.6	239.1	239.2	40.5	874.0
40,0°	166.2	166.4	164.7	163.3	162.9	163.0	29.6	903.6
42,5°	115.3	113.5	111.1	110.0	109.8	109.7	21.3	924.9
45,0°	79.0	76.9	75.1	74.3	74.0	73.9	15.2	940.1
47,5°	56.0	54.4	53.1	52.3	51.9	51.7	11.2	951.3
50,0°	40.9	39.8	38.8	38.0	37.5	37.4	8.5	959.8
52,5°	31.8	30.8	29.9	29.1	28.8	28.7	6.8	966.6
55,0°	25.9	25.0	24.2	23.4	23.2	23.3	5.6	972.3
57,5°	21.7	20.8	20.1	19.5	19.4	19.6	4.8	977.0
60,0°	18.6	18.0	17.1	16.6	16.8	17.1	4.2	981.2
62,5°	16.0	15.6	14.7	14.4	14.7	15.1	3.6	984.8
65,0°	14.0	13.6	12.8	12.7	13.1	13.5	3.2	988.1
67,5°	12.0	12.1	11.2	11.1	11.6	12.1	2.9	991.0
70,0°	9.8	10.4	9.7	9.7	10.2	10.6	2.5	993.4
72,5°	7.8	8.3	8.3	8.3	8.8	9.1	2.1	995.5
75,0°	6.2	6.3	6.8	6.9	7.3	7.6	1.6	997.1
77,5°	4.6	4.9	5.3	5.5	5.8	6.0	1.3	998.4
80,0°	3.1	3.4	3.7	4.0	4.2	4.4	0.9	999.2
82,5°	1.8	2.1	2.4	2.6	2.8	2.9	0.5	999.7
85,0°	0.7	1.0	1.2	1.3	1.6	1.6	0.2	1000.0
87,5°	0.3	0.3	0.3	0.3	0.4	0.4	0.1	1000.0

Photometric test report

Family Highbay 21	Order number: 52HN12DB4QDA03 EAN: 4069025421845	LP number 59723_168
UGR-Table	Standard room	siteco

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.2	20.4	19.5	20.7	21.0	19.0	20.2	19.4	20.5	20.9
	3H	19.2	20.3	19.6	20.6	21.0	19.1	20.2	19.5	20.5	20.8
	4H	19.2	20.2	19.6	20.6	20.9	19.1	20.1	19.5	20.5	20.9
	6H	19.2	20.1	19.6	20.5	20.9	19.2	20.1	19.6	20.4	20.8
	8H	19.3	20.0	19.7	20.4	20.8	19.3	20.0	19.7	20.4	20.8
	12H	19.3	19.9	19.7	20.3	20.8	19.3	20.0	19.7	20.4	20.8
4H	2H	19.1	20.1	19.5	20.4	20.8	18.9	19.9	19.3	20.3	20.6
	3H	19.2	20.0	19.6	20.4	20.8	19.1	19.9	19.5	20.3	20.7
	4H	19.2	19.9	19.6	20.3	20.8	19.1	19.9	19.6	20.3	20.7
	6H	19.2	19.8	19.7	20.2	20.7	19.2	19.8	19.7	20.3	20.8
	8H	19.2	19.7	19.6	20.2	20.6	19.3	19.8	19.7	20.3	20.7
	12H	19.2	19.6	19.7	20.1	20.6	19.3	19.7	19.8	20.2	20.7
8H	4H	19.1	19.7	19.6	20.1	20.6	19.1	19.6	19.6	20.1	20.6
	6H	19.1	19.6	19.6	20.1	20.6	19.2	19.6	19.7	20.1	20.6
	8H	19.1	19.5	19.6	20.0	20.5	19.2	19.6	19.7	20.1	20.6
	12H	19.1	19.4	19.6	19.9	20.5	19.3	19.6	19.8	20.1	20.6
12H	4H	19.2	19.6	19.7	20.1	20.6	19.1	19.5	19.6	20.0	20.5
	6H	19.2	19.5	19.7	20.0	20.5	19.2	19.5	19.7	20.0	20.6
	8H	19.1	19.4	19.6	19.9	20.5	19.2	19.5	19.8	20.0	20.6

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:				L = 852 B = 264		
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
		Luminance in cd/m²								
γ										
45,0°	19646.3	19038.2	19324.3	19431.7	19471.8	19038.7	18362.3	17859.9	17694.2	17645.5
50,0°	11145.0	10837.9	11040.8	11066.1	11064.6	10854.8	10465.0	10117.2	9896.3	9818.7
55,0°	7545.6	7324.8	7487.8	7679.0	7885.3	7734.2	7351.5	7044.4	6852.4	6875.8
60,0°	5805.2	5637.9	5732.8	6137.4	6330.3	6319.8	6088.0	5715.2	5648.7	5767.0
65,0°	5223.6	4919.9	4814.4	5210.8	5450.4	5605.9	5448.2	5082.3	5175.7	5407.1
70,0°	4662.5	4403.4	4260.5	4719.3	4616.0	4789.2	5124.3	4768.7	4957.8	5255.2
75,0°	3834.2	3701.4	3718.4	3680.8	3794.0	4010.0	4133.2	4501.0	4675.4	4960.9
80,0°	2500.4	2420.4	2575.2	2671.6	2716.1	2969.1	3305.9	3738.8	4018.2	4254.5
85,0°	977.0	952.4	968.3	973.1	1064.0	1341.2	1889.9	2353.4	2885.9	3146.0

Photometric test report

Family
Highbay 21

Order number: 52HN12DB4QDA03
EAN: 4069025421845

LP number
59723_168

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN12DB4QDA03 EAN: 4069025421845	LP number 59723_168
Dimming levels table environmental temperature: 25°C		

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	38000	197.7
95	241	252	36142	187.3
90	228	250	34270	177.1
85	214	248	32244	166.1
80	201	245	30347	155.8
75	188	243	28447	145.8
70	175	240	26529	135.6
65	163	238	24754	126.2
60	150	235	22825	116.2
55	137	231	20886	106.1
50	124	228	18947	96.3
45	112	224	17141	87.1
40	99	219	15170	77.2
35	87	215	13346	68.0
30	74	209	11364	58.3
25	62	202	9525	49.1
20	50	194	7676	40.2
15	37	183	5668	30.6
10	25	169	3806	21.8
5	13	145	1934	12.5
1	4	102	528	5.4