

**Order No.:** 5MT317D04WD | **GTIN (EAN):** 4058352219089


**Product description:** Tar21,LED7360lm840,DA,sp



Taris® 21, office luminaire, primary anti-glare with micro louvre, primary optical cover: axial lens, of PMMA, structured, CAT 2 ( $L \leq 1500 \text{cd/m}^2$ ), light emission: direct/indirect distribution, primary light characteristic: symmetric, installation type: suspended mounting, LED, rated luminous flux: 7.360lm, luminous efficacy: 172lm/W, light colour: 840, colour temperature: 4000K, control gear: ECG DALI, with terminal, 5-pole, mains connection: 230V, AC, 50Hz, rated input power: 43W, housing, luminaire housing, of plastic, pure white, length: 1.510mm, width: 134mm, height: 50mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, protection symbol: F, impact resistance: IK02, permissible operating ambient temperature: 0...+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	5.0
GTIN (EAN):	4058352219089



Order No.: 5MT317D04WD | GTIN (EAN): 4058352219089

Detailed technical description: Tar21,LED7360lm840,DA,sp



#### Key data

- Product type: office luminaire
- Product name: Taris® 21
- Order No.: 5MT317D04WD

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Cover: axial lens, structured
- Glare reduction: micro louver
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct/indirect distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 19$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 7360lm
- Luminous efficacy: 172lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 43W

#### Operating device:

- Control gear: ECG DALI
- Control: DALI

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Protection symbol: F
- Temperature range (operation): 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

#### Material, Colour

- housing: plastic, pure white
- luminaire housing: plastic, pure white
- Colour specification: pure white
- Cover: axial lens of PMMA

#### Mounting

- Mounting method, mounting location: suspended mounting
- Arrangement: single arrangement

#### Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 230V, 230..240V, 50Hz, AC

#### Dimensions, Weight


- Length: 1510mm
- Width: 134mm
- Height: 50mm
- Weight: 5.0kg

#### Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 5MT317D04WD | GTIN (EAN): 4058352219089

Dimensions: Tar21,LED7360lm840,DA,sp



Order No.: 5MT317D04WD | GTIN (EAN): 4058352219089


Planning data: Tar21,LED7360lm840,DA,sp

**5MT317D04WD: 1x LED**

4058352219089

5MT317D04WD

LED 4000 K | CRI ≥ 80  $\phi_{\text{N}}$  7360 lm



$\phi_{\downarrow}$  81%  $\phi_{\uparrow}$  19%

Luminance values (cd/m<sup>2</sup>)

	C 0/180	C 90/270
L <sub>80</sub>	1244	1846
L <sub>70</sub>	1365	2686
L <sub>65</sub>	1341	2998

UGR 16.2 17.4

X 4H Y 8H  $\rho$  70/50/20 S 0.25H

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 01.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -