

Order No.: 5TS103A0Q | **GTIN (EAN):** 4039806907080


Product description: Modario, trunk.rail, 3lg, L4485, 10x2.5², wh



Modario® IP64, trunking rail, of sheet steel, galvanised, coated, pure white, 3-length, length: 4.485 mm, width: 58 mm, height: 43mm, through-wiring: 10x 2.5mm², with terminal, 10-pole, max. 2.5mm², protection rating (complete): for IP64 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: EN 60598, packaging unit: 1 piece



Wt. (kg): 6.4
 GTIN (EAN): 4039806907080



Order No.: 5TS103A0Q | GTIN (EAN): 4039806907080

Detailed technical description: Mod64, trunk.rail, 3lg, L4485, 10x2.5², wh



Key data

- Product type: trunking components group (TS)
- Product name: Modario® IP64
- Order No.: 5TS103A0Q

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for electrical and mechanical plug and socket connection of rail elements

Certificates, Standards

- Protection rating: for IP64 protection rating
- Insulation class: insulation class I (protective earthing)
- Standard: EN 60598
- Certification, designation: CE, ENEC, VDE

Material, Colour

- trunking rail: sheet steel, galvanised, coated, pure white, 3-length
- Colour specification: pure white

Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling
- Arrangement: single/continuous arrangement

Electrical connection

- Connection: terminal, 10-pole, max. 2.5mm²
- Through-wiring: 10x 2.5mm²

Dimensions, Weight

- System units: 15x SE
- Length: 4485mm
- Width: 58mm
- Height: 43mm
- Mounting distance: max. 3.5m
- Weight: 6.4kg

Order No.: 5TS103A0Q | GTIN (EAN): 4039806907080

Dimensions: Mod64, trunk.rail, 3lg, L4485, 10x2.5², wh

