

**Order No.:** 5XA7680E3B00C | **GTIN (EAN):** 4058352234389

**Product description:** FL20md,LED-unit,RS17,750,208/306W



Floodlight FL 20 midi, LED unit, primary light control with lens, of plastic, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: RS17, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 750, colour temperature: 5000K, with cable with plug, mains connection: 220..240V, AC, 50/60Hz, rated input power: 208W/306W, LED unit, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 402mm, width: 421mm, height: 57mm, protection rating (complete): IP66, packaging unit: 1 piece

IP 66

Lamps:	LED
Wt. (kg):	6.5
GTIN (EAN):	4058352234389

**Order No.:** 5XA7680E3B00C | **GTIN (EAN):** 4058352234389

**Detailed technical description:** FL20md,LED-unit,RS17,750,208/306W



#### Key data

- Product type: LED unit
- Product name: Floodlight FL 20 midi
- Order No.: 5XA7680E3B00C

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Light control: lens of plastic
- Cover: cover panel, transparent
- Light distribution: RS17
- Symmetry: asymmetric distribution
- Light emission: direct distribution

#### Lamps:

- Lamps: High Power LED, LED
- Colour temperature: 5000K
- Colour rendering index: CRI > 70
- Light colour: 750
- Rated input power: 208W/306W

#### Certificates, Standards

- Protection rating: IP66

#### Material, Colour

- LED unit: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S)
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

#### Mounting

- Mounting method, mounting location: screw fastening, in housing

#### Electrical connection

- Connection: cable with plug
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 402mm
- Width: 421mm
- Height: 57mm
- Weight: 6.5kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 16.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -