

**Order No.:** 51TR1CB | **GTIN (EAN):** 4058352241875

**Product description:** Lic, trunk.rail, L1500, 11x2.5<sup>2</sup>, wh



Licross®, trunking rail, of sheet steel, galvanised, coil coated, white, length: 1.500 mm, width: 64 mm, height: 67mm, through-wiring: 11x 2.5mm<sup>2</sup>, protection rating (complete): maximum IP64, depends on used inserts and accessories, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece



Wt. (kg): 2.7  
GTIN (EAN): 4058352241875



Order No.: 51TR1CB | GTIN (EAN): 4058352241875

Detailed technical description: Lic,trunk.rail,L1500,11x2.5<sup>2</sup>,wh



#### Key data

- Product type: trunking components group (TS)
- Product name: Licross®
- Order No.: 51TR1CB

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: halogen-free wiring

##### Certificates, Standards

- Protection rating: maximum IP64, depends on used inserts and accessories
- Insulation class: insulation class I (protective earthing)
- Supplement: LABS conformity tested according to VDMA 24364:2018-05
- Certification, designation: CE, UKCA

##### Material, Colour

- trunking rail: sheet steel, galvanised, coil coated, white
- Colour specification: white

##### Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling
- Arrangement: single/continuous arrangement
- Supplement: only suitable for indoor use

##### Electrical connection

- Through-wiring: 11x 2.5mm<sup>2</sup>

##### Dimensions, Weight

- Length: 1500mm
- Width: 64mm
- Height: 67mm
- Weight: 2.7kg

Order No.: 51TR1CB | GTIN (EAN): 4058352241875

Dimensions: Lic,trunk.rail,L1500,11x2.5<sup>2</sup>,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 27.10.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -