

Order No.: 5XA1573K1B2 | GTIN (EAN): 4058352167816

Product description: SmBell,GT,ST1.2a,1750lm740,Plus



electrics components group, for Small Bell, control gear: ECG Plus, LED
luminous flux: 1.750 lm, colour temperature: 4000K, mains connection:
230..240V, AC, 50/60Hz, start of lifetime: 13 W, end of service life: 14 W,
reduction: 7 W, primary light characteristic: asymmetric, primary optical cover:
enclosure, of PMMA, transparent structured, gear tray with cover, insulation
class (complete): insulation class II (safety insulation), certification: CE, ENEC,
VDE



Lamps:	LED
Wt. (kg):	1.9
GTIN (EAN):	4058352167816

Order No.: 5XA1573K1B2 | GTIN (EAN): 4058352167816

Detailed technical description: SmBell,GT,ST1.2a,1750lm740,Plus



Key data

- Product type: electrics components group
- Product name: Small Bell
- Order No.: 5XA1573K1B2

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, aluminium vaporised
- Cover: enclosure, transparent structured
- Light distribution: ST1.2a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 1750lm
- Luminous efficacy: 133lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740
- Rated input power begin service life: 13
- Rated input power end service life: 14
- Rated input power at 50% lumin. flux: 7

Operating device:

- Control gear: ECG Plus
- Control: Plus
- Equipment: power reduction, digital communication interface, constant luminous flux control, time-dependent luminous flux control, flexible luminous flux parameterisation
- Switching method: electronic power reduction

Certificates, Standards

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

Material, Colour

- Cover: enclosure of PMMA

Electrical connection

- Nominal voltage: 230..240V, 50/60Hz, AC
- Surge voltage resistance: 6kV 1.2/50µs

Dimensions, Weight

- Weight: 1.9kg

Light emission

- Light emission: < 3%