

Order No.: 5XA768000ZS00185XX | **GTIN (EAN):** 4058352495018

Product description: SiST.MAXIRI,LED,70630lm830,ECG,TSG,dir



SiSTELLAR MAXI, refurbishment insert, primary light control with lens, of plastic, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: PL43, light emission: direct distribution, primary light characteristic: asymmetric, LED, High Power LED, rated luminous flux: 70.630lm, light colour: 830, colour temperature: 3000K, control gear: ECG, mains connection: 220..240V, AC, 50/60Hz, connection cable pre-assembled, rated input power: 624W, LED unit, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, packaging unit: 1 piece

IP 54  

Lamps:	LED
Wt. (kg):	40.5
GTIN (EAN):	4058352495018

Order No.: 5XA768000ZS00185XX | GTIN (EAN): 4058352495018

Detailed technical description: SiST.MAXIRI,LED,70630lm830,ECG,TSG,dir



Key data

- Product type: refurbishment insert
- Product name: SiSTELLAR MAXI
- Order No.: 5XA768000ZS00185XX

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Cover: cover panel, transparent
- Light distribution: PL43
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Lamps: High Power LED, LED
- Rated luminous flux: 70630lm
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- Rated input power: 624W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE

Material, Colour

- LED unit: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S)
- Quantity: 3 piece
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC
- Connection cable: pre-assembled

Dimensions, Weight

- Weight: 40.5kg