ѕітесо

Order No.: 59LJ201 | GTIN (EAN): 4058352612361 Product description: Ecop31multisens,PIR-sens,surf



Ecopack[®] 31, multi-sensor, installation type: surface-mounted, housing, of PC/ABS, traffic white (RAL 9016), length: 149mm, width: 56mm, height: 28mm, PIR sensor, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK02, permissible operating ambient temperature: -10..+35°C, packaging unit: 1 piece

| IP 20 | | CE |
|-------|--|----|
|-------|--|----|

Wt. (kg): 0.1 GTIN (EAN): 4058352612361

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 24.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 59LJ201 | GTIN (EAN): 4058352612361 Detailed technical description: Ecop31multisens,PIR-sens,surf

Key data

- Product type: multi-sensor
- Product name: Ecopack® 31
- Order No.: 59LJ201

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): -10..+35°C
- Certification, designation: CE

Material, Colour

- housing: PC/ABS, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)

Mounting

 Mounting method, mounting location: surface-mounted, to the luminaire

Dimensions, Weight

- Length: 149mm
- Width: 56mm
- Height: 28mm
- Weight: 0.1kg

Service life

- Rated service life: 50000h at AT = 25°C

Inputs

1x PIR movement sensor

- Option: switching time adjustable between 5 seconds - 30 minutes
- Feature: for motion detection, circular detection area

1x light sensor

 Option: daylight threshold adjustable from 2..50lx