ѕітесо

Order No.: 5LZ9050AYA | GTIN (EAN): 4058352692851 Product description: SCon,sensD3,centCtrl,lightsens





SITECO Connectlight sensor D3, central control - connection to lighting or building management, dimmable, installation type: surface-mounted, installation location: to the wall, of plastic, protection rating (complete): IP65, certification: CE, 1 x light sensor, 1 x DALI, packaging unit: 1 piece

```
IP 65 (E
```

Wt. (kg): 0.1 GTIN (EAN): 4058352692851

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5LZ9050AYA | GTIN (EAN): 4058352692851 Detailed technical description: SCon,sensD3,centCtrl,lightsens



Key data

- System family: SITECO Connect 21H
- Product type: lighting management
- components Product name:
- Product name: SITECO Connect
 Order No : 51 790504X4
- Order No.: 5LZ9050AYA

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP65
- Temperature range (operation): -35..+70°C
- Certification, designation: CE

Material, Colour

- surface-mounted housing: plastic, black
- Colour specification: black

Mounting

- Mounting method, mounting location: surface-mounted, to the wall
- Supplement: for mounting in indoor and outdoor areas

Dimensions, Weight

- Width: 87mm
- Height: 148mm
- Weight: 0.1kg

Inputs

1x light sensor

- Connection: light sensor
- Illuminance: 1..100000lx
- Option: usability at high altitudes

Outputs

1x DALI

- System current: max. 10mA