

Order No.: 5EA40EHC01 | GTIN (EAN): 4058352641323

Product description: SConWi,SmartPlugCelMotHigh



SITECO Connect WirelessSmart Plug Cellular Motion High, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, D4i, local mesh radio network, EGPRS, NB-IoT NB2, LTE Cat M1, 5G, 4G, 2G, 2.4GHz, remote setup and operation, local setting and operation with USB stick, local setting and operation with smartphone app, manual, by time, by timer, by weekday, by AstroDim calendar, by daylight, by movement, via API, with radio clock, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, GPS, GNSS, GLONASS, GALILEO, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1
GTIN (EAN): 4058352641323

Order No.: 5EA40EHC01 | GTIN (EAN): 4058352641323

Detailed technical description: SConWi,SmartPlugCelMotHigh



Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40EHC01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: plastic, transparent, colour-backed, dark grey
- Colour specification: dark grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 6..12m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor

- Detection range: D max. 18m



Y axis

Order No.: 5EA40EHCC
Dimensions: SConWi, Sma

Mounting height	X axis	Y axis
7.0 m	11.9 m	12.4 m
8.0 m	13.6 m	14.2 m
9.0 m	15.3 m	15.9 m
10.0 m	17.0 m	17.7 m