

Order No.: 5EA40ELC01 | GTIN (EAN): 4058352641347

Product description: SConWi,SmartPlugCelMotLow




SITECO Connect WirelessSmart Plug Cellular Motion Low, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, D4i, local mesh radio network, EGPRS, NB-IoT NB2, LTE Cat M1, 5G, 4G, 2G, 2.4GHz, remote setup and operation, local setting and operation with USB stick, local setting and operation with smartphone app, manual, by time, by timer, by weekday, by AstroDim calendar, by daylight, by movement, via API, with radio clock, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, GPS, GNSS, GLONASS, GALILEO, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352641347

Order No.: 5EA40ELC01 | GTIN (EAN): 4058352641347

Detailed technical description: SConWi,SmartPlugCelMotLow



#### Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40ELC01

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: D4i, Smart Interface below

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: plastic, transparent, colour-backed, dark grey
- Colour specification: dark grey

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 0..6m

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Weight: 0.1kg

#### Inputs

#### PIR movement sensor

- Detection range: D max. 11m



Y axis

---

**Order No.:** 5EA40ELCG

**Dimensions:** SConWi, Sma

<b>Mounting height</b>	<b>X axis</b>	<b>Y axis</b>
5.0 m	8.5 m	8.8 m
6.0 m	10.2 m	10.6 m