

**Order No.:** 5LS90800ED | **GTIN (EAN):** 4039806166531

**Product description:** DUSIP60, fixed ins, sh. steel, wh



DUS® IP60, fixed insert, of sheet steel, coated, pure white, length: 1.535mm, width: 60mm, height: 45mm, system units: 307mm, for production/manufacturing, retail areas, ancillary rooms, corridors and circulation routes, office rooms, protection rating (complete): IP20 / IP60, insulation class (complete): insulation class I (protective earthing), IP60 for complete trunking system achieved in combination with suitable IP60 components, packaging unit: 1 piece

IP 20 IP 60



Wt. (kg): 0.8  
GTIN (EAN): 4039806166531

**Order No.:** 5LS90800ED | **GTIN (EAN):** 4039806166531

**Detailed technical description:** DUSIP60, fixed ins, sh. steel, wh



#### Key data

- Product type: fixed insert
- Product name: DUS® IP60
- Order No.: 5LS90800ED

#### Certificates, Standards

- Protection rating: IP20 / IP60
- Insulation class: insulation class I (protective earthing)
- Supplement: IP60 for complete trunking system achieved in combination with suitable IP60 components

#### Material, Colour

- fixed insert: sheet steel, coated, pure white
- Colour specification: pure white

#### Dimensions, Weight

- System units: 5x SE
- Length: 1535mm
- Width: 60mm
- Height: 45mm
- Weight: 0.8kg