

Order No.: 59HL94001 | GTIN (EAN): 4058352379325

Product description: HB11basemod,surf



Highbay 11Interface MD, master, local control, dimmable, installation type: surface-mounted, installation location: to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 230V, voltage type: AC, 1 x DALI, packaging unit: 1 piece

IP 54  

Wt. (kg): 0.3
GTIN (EAN): 4058352379325

Order No.: 59HL94001 | GTIN (EAN): 4058352379325

Detailed technical description: HB11basemod,surf



Key data

- Product type: base module
- Product name: Highbay 11
- Order No.: 59HL94001

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE

Material, Colour

- housing: plastic, white, square
- Colour specification: white
- mounting bracket: steel, galvanised

Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire
- Supplement: only for mounting indoors

Electrical connection

- Nominal voltage: 230V, 50Hz, AC

Dimensions, Weight

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.3kg

Outputs

1x DALI

- Connection: screw terminal, 2-pole, max. 4mm²
- Feature: DALI, master function, broadcast addressing, max. 30 DALI ECGs