

Order No.: 51TS12TNT75W | **GTIN (EAN):** 4058352298558

Product description: Lic11Pr,wd,7740lm8tw,DT8,IP50,L1500,wh



Licross® 11 Protected TW, luminaire insert, of sheet steel, galvanised, coil coated, white, length: 1.500mm, width: 90mm, height: 101mm, LED rated luminous flux: 7.740lm, light colour: 8tw, control gear: DALI DT8, control gear: ECG DALI, with plug, 5-pole, with phase selection, mains connection: 220..240V, AC, 50/60Hz, rated input power: 57W, halogen-free wiring, primary optical cover: cover, of PMMA, light emission: direct distribution, primary light characteristic: symmetric, protection rating (complete): IP50, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories, impact resistance: IK06, permissible ambient temperature for indoor applications: -25..+40°C, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece



Lamps:	LED
Wt. (kg):	2.9
GTIN (EAN):	4058352298558



Order No.: 51TS12TNT75W | **GTIN (EAN):** 4058352298558

Detailed technical description: Lic11Pr,wd,7740lm8tw,DT8,IP50,L1500,wh



Key data

- Product type: luminaire insert
- Product name: Licross® 11 Protected TW
- Order No.: 51TS12TNT75W

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: cover
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 7740lm
- Luminous efficacy: 135lm/W
- Colour temperature: 2700..6500K
- Colour rendering index: CRI > 80
- Light colour: 8tw
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 57W
- Supplement: halogen-free wiring

Operating device:

- Control gear: ECG DALI
- Control: DALI DT8

Certificates, Standards

- Protection rating: IP50
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK06
- Protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories
- Temperature range (operation): -25..+40°C
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, LABS conformity tested according to VDMA 24364:2018-05
- Certification, designation: CE, ENEC, VDE, UKCA

Material, Colour

- Licross® LED insert: sheet steel, galvanised, coil coated, white
- Colour specification: white
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail
- Arrangement: single/continuous arrangement
- Supplement: only suitable for indoor use

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 1500mm
- Width: 90mm
- Height: 101mm
- Weight: 2.9kg

Service life

- Rated service life: 100000h (L85/B50) at AT = 25°C

Order No.: 51TS12TNT75W | GTIN (EAN): 4058352298558

Dimensions: Lic11Pr,wd,7740lm8tw,DT8,IP50,L1500,wh




Order No.: 51TS12TNT75W | GTIN (EAN): 4058352298558

Planning data: Lic11Pr,wd,7740lm8tw,DT8,IP50,L1500,wh

**51TS12TNT75W: 1x LED;
individual setting**

4058352298558
51TS12TNT75W
LED 2700 K ... 6500 K | CRI ≥ 80
φ_N 7740 lm



φ_↓ 97% φ_↑ 3%


Luminance values (cd/m²)

	C 0/180	C 90/270
L ₈₀	9637	8472
L ₇₀	8814	12026
L ₆₅	8805	14147

UGR 24.7 24.8
X 4H Y 8H ρ 70/50/20 S 0.25H

**51TS12TNT75W: 1x LED;
factory setting**

4058352298558
51TS12TNT75W
LED 2700 K ... 6500 K | CRI ≥ 80
φ_N 7740 lm



φ_↓ 97% φ_↑ 3%


Luminance values (cd/m²)

	C 0/180	C 90/270
L ₈₀	9637	8472
L ₇₀	8814	12026
L ₆₅	8805	14147

UGR 24.7 24.8
X 4H Y 8H ρ 70/50/20 S 0.25H

**51TS12TNT75W: 1x LED;
individual setting**

4058352298558
51TS12TNT75W
LED 2700 K ... 6500 K | CRI ≥ 80
φ_N 7740 lm



φ_↓ 97% φ_↑ 3%

Luminance values (cd/m²)

	C 0/180	C 90/270
L ₈₀	9637	8472
L ₇₀	8814	12026
L ₆₅	8805	14147

UGR 24.7 24.8
X 4H Y 8H ρ 70/50/20 S 0.25H