

Order No.: 59US1FCMA | GTIN (EAN): 4058352363768

Product description: SConbasemod, surf



SITECO ConnectExternal Interface MD, master, local control, dimmable, installation type: surface-mounted, installation location: to the ceiling, to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, VDE, voltage: 230V, voltage type: AC, packaging unit: 1 piece

<u>Ď¥</u> IP 54 ☐ (€

Wt. (kg): 0.1

GTIN (EAN): 4058352363768



Order No.: 59US1FCMA | GTIN (EAN): 4058352363768

Detailed technical description: SConbasemod, surf



Key data

- System family: SITECO Connect 31 Logistic DALI
- Product type: base moduleProduct name: SITECO ConnectOrder No.: 59US1FCMA

Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, VDE

Material, Colour

- housing: plastic, white, square
- Colour specification: white

Mounting

 Mounting method, mounting location: surface-mounted, to the ceiling, to the luminaire

Electrical connection

- Nominal voltage: 230V, 50Hz, AC

Dimensions, Weight

Length: 83mmWidth: 83mmHeight: 28mmWeight: 0.1kg