

**Order No.:** 51MX22TBT5B | **GTIN (EAN):** 4058352687239

**Product description:** Sil21,ELD-Lbk,4650lm8tw,DT8,L1504,bk



Silica® 21, office luminaire, primary light control with darklight reflector, of PMMA, black, CAT 2 ( $L \leq 3000 \text{cd/m}^2$ ), light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 4.650lm, luminous efficacy: 110lm/W, light colour: 8tw, colour temperature: 2700..6500K, control gear: ECG DALI, with terminal, 3+2-pole, max. 2.5mm<sup>2</sup>, mains connection: 220..240V, AC, 50/60Hz, rated input power: 42.2W, luminaire housing, of aluminium, jet black (RAL 9005), length: 1.504mm, width: 53mm, height: 53mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, permissible operating ambient temperature: 0..+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	3.5
GTIN (EAN):	4058352687239



**Order No.:** 51MX22TBT5B | **GTIN (EAN):** 4058352687239

**Detailed technical description:** Sil21,ELD-Lbk,4650lm8tw,DT8,L1504,bk



#### Key data

- Product type: office luminaire
- Product name: Silica® 21
- Order No.: 51MX22TBT5B

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Light control: darklight reflector of PMMA, black
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 19$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 4650lm
- Luminous efficacy: 110lm/W
- Colour temperature: 2700..6500K
- Colour rendering index: CRI > 80
- Light colour: 8tw
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 42.2W

#### Operating device:

- Control gear: ECG DALI
- Control: DALI DT8

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

#### Material, Colour

- luminaire housing: aluminium, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)

#### Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling
- Arrangement: single arrangement

#### Electrical connection

- Connection: terminal, 3+2-pole, max. 2.5mm<sup>2</sup>
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 1504mm
- Width: 53mm
- Height: 53mm
- Weight: 3.5kg

#### Service life

- Rated service life: 50000h (L85/B50) at AT = 25°C

Order No.: 51MX22TBT5B | GTIN (EAN): 4058352687239

Dimensions: Sil21,ELD-Lbk,4650lm8tw,DT8,L1504,bk

