

Order No.: 5LZ905950 | **GTIN (EAN):** 4058352668863

Product description: SCon21H,controller,wired



SITECO Connect 21Hcontroller, master, central control - connection to lighting or building management, dimmable, installation type: recessed, installation location: in an electrical distributor, of plastic, part units: 6 part units, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, voltage: 100..240V, voltage type: AC, 1 x network connector Ethernet, 1 x USB/WiFi, 3 x service push button, 4 x DALI-2, 1 x status LED, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.5
GTIN (EAN): 4058352668863

Order No.: 5LZ905950 | **GTIN (EAN):** 4058352668863

Detailed technical description: SCon21H,controller,wired



Key data

- System family: SITECO Connect 21H
- Product type: control unit
- Product name: SITECO Connect 21H
- Order No.: 5LZ905950

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0...+40°C
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, bright grey, 6 part units
- Colour specification: bright grey

Mounting

- Mounting method, mounting location: recessed, in an electrical distributor
- Supplement: only suitable for use in indoor areas

Electrical connection

- Nominal voltage: 100...240V, 50/60Hz, AC

Dimensions, Weight

- Length: 91mm
- Width: 107mm
- Height: 62mm
- Weight: 0.5kg

Inputs

3x service push button

- Option: for manual control and basic system setting

Outputs

4x DALI-2

- System current: DALI current 250mA per DALI line
- Feature: maximum 64 ECG DALI and maximum 63 certified DALI2 sensors/push button interfaces connectable per DALI line, HCLlive function in combination with ECG DT8, averaging with connected light sensors, connection of DALI2 certified sensors