

**Order No.:** 5TR305FCMA | **GTIN (EAN):** 4058352635704

**Product description:** Mod31Intbasemod



Modario® 31 Interface MD, master, local control - self-sufficient standalone sensors, dimmable, installation location: to the Modario® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, VDE, voltage: 230V, voltage type: AC, 1 x DALI, packaging unit: 1 piece



Wt. (kg): 0.4  
GTIN (EAN): 4058352635704

**Order No.:** 5TR305FCMA | **GTIN (EAN):** 4058352635704

**Detailed technical description:** Mod31Intbasemod



#### Key data

- System family: SITECO Connect 31 Logistic DALI
- Product type: base module
- Product name: Modario® 31 Interface
- Order No.: 5TR305FCMA

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: internal wiring halogen-free

##### Operating device:

- Control: DALI, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20...+50°C
- Certification, designation: CE, VDE

#### Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

#### Mounting

- Supplement: only suitable for use in indoor areas

#### Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50Hz, AC

#### Dimensions, Weight

- Length: 597mm
- Width: 96mm
- Height: 97mm
- Weight: 0.4kg

#### Outputs

##### DALI

- Feature: DALI, master function, broadcast addressing, max. 30 DALI ECGs

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -