

Order No.: 5TR305FCMA | GTIN (EAN): 4058352635704

**Product description: Mod31Intbasemod**



Modario® 31 Interface MD, master, local control, dimmable,  
installation location: to the Modario® trunking rail, of sheet steel, protection  
rating (complete): IP20, insulation class (complete): insulation class I  
(protective earthing), certification: CE, VDE, voltage: 230V, voltage type: AC, 1  
x DALI, packaging unit: 1 piece

 IP 20  

Wt. (kg): 0.4  
GTIN (EAN): 4058352635704

Order No.: 5TR305FCMA | GTIN (EAN): 4058352635704

Detailed technical description: Mod31Intbasemod



#### Key data

- System family: SITECO Connect 31 Logistic DALI
- Product type: base module
- Product name: Modario® 31 Interface
- Order No.: 5TR305FCMA

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: halogen-free wiring

##### Operating device:

- Control: DALI, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, VDE

#### Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

#### Mounting

- Supplement: only suitable for indoor use

#### Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50Hz, AC

#### Dimensions, Weight

- Length: 500mm
- Width: 96mm
- Height: 97mm
- Weight: 0.4kg

#### Outputs

##### DALI

- Feature: DALI, master function, broadcast addressing, max. 30 DALI ECGs