

Order No.: 5XA7672B0000C | **GTIN (EAN):** 4058352236444

Product description: FL20mn,hous,PlusDA,51W,IC2



Floodlight FL 20 mini, housing, primary light characteristic: asymmetric, control gear: ECG Plus, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 51W, housing frame, housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 446mm, width: 355mm, height: 62mm, DALI, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, standard: DIN EN 12944, packaging unit: 1 piece



Wt. (kg): 2.9
GTIN (EAN): 4058352236444

Order No.: 5XA7672B0000C | **GTIN (EAN):** 4058352236444

Detailed technical description: FL20mn,hous,PlusDA,51W,IC2



Key data

- Product type: housing
- Product name: Floodlight FL 20 mini
- Order No.: 5XA7672B0000C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 51W

Operating device:

- Control gear: ECG Plus
- Control: Plus/DALI
- Switching method: electronic power reduction

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class II (safety insulation)
- Standard: DIN EN 12944
- Certification, designation: CE, ENEC, VDE

Material, Colour

- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: Siteco® metallic grey (DB 702S)

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC
- Surge voltage resistance: 10kV 1.2/50µs

Dimensions, Weight

- Length: 446mm
- Width: 355mm
- Height: 62mm
- Weight: 2.9kg