siteco

Order No.: 5LZ960100 | **GTIN (EAN):** 4058352651612

Product description: SCon21B,controller,wired

SITECO Connect 21Bcontroller, master, central control, dimmable, installation type: recessed, installation location: in an electrical distributor, part units: 12 part units, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, voltage: 100..240V, voltage type: AC, 1 x network connector Ethernet, 1 x USB/WiFi, 3 x service push button, 2 x DALI-2, 1 x status LED, packaging unit: 1 piece

IP 20

Wt. (kg):	0.2
GTIN (EAN):	4058352651612

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 30.08.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 5LZ960100 | **GTIN (EAN):** 4058352651612

Detailed technical description: SCon21B,controller,wired

Key data
- System family: SITECO Connect 21B
- Product type: control unit
- Product name: SITECO Connect 21B
- Order No.: 5LZ960100

Lighting technology | Lamps | Control gear

Component 1

Operating device:
- Control: DALI 2, dimmable

Certificates, Standards
- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Mounting
- Mounting method, mounting location: recessed, in an electrical distributor
- Supplement: only suitable for indoor use

Electrical connection
- Connection: terminal, 2-pole, max. 1.5mm²
- Nominal voltage: 100..240V, 50/60Hz, AC

Dimensions, Weight
- Weight: 0.2kg

Inputs

3x service push button
- Option: for manual control and basic system setting

Outputs

2x DALI-2
- Connection: screw terminal, 2-pole, max. 1.5mm²
- System current: DALI current 250mA per DALI line
- Feature: maximum 64 ECG DALI and maximum 63 certified DALI2 sensors/push button interfaces connectable per DALI line, HCLlive function in combination with ECG DT8, averaging with connected light sensors, connection of DALI2 certified sensors

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com