

**Order No.:** 51MQ17WD2612 | **GTIN (EAN):** 4058352528013

**Product description:** APO21I,1545x307,6900lm865,DA2,IP50



Apollon 21 linear, office luminaire, primary optical cover: micro prismatic cover, CAT 2 ( $L \leq 3000 \text{cd/m}^2$ ), light emission: direct distribution, primary light characteristic: symmetric, installation type: lay-in mounting, LED, rated luminous flux: 6.900lm, luminous efficacy: 115lm/W, light colour: 865, colour temperature: 6500K, control gear: DALI 2, with terminal, 5-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 60W, housing, of aluminium, coated, pure white, length: 1.545mm, width: 307mm, height: 48mm, housing upper side, of sheet steel, galvanised, protection rating (complete): IP20, protection rating (lamp compartment, on room side): IP50, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, packaging unit: 1 piece



Lamps:	LED
Wt. (kg):	3.7
GTIN (EAN):	4058352528013

**Order No.:** 51MQ17WD2612 | **GTIN (EAN):** 4058352528013

**Detailed technical description:** APO21I,1545x307,6900lm865,DA2,IP50



#### Key data

- Product type: office luminaire
- Product name: Apollon 21 linear
- Order No.: 51MQ17WD2612

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Cover: micro prismatic cover
- Beam angle: wide distribution, 80°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 22$
- UGR viewing direction along lateral luminaire axis:  $\leq 22$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 6900lm
- Luminous efficacy: 115lm/W
- Colour temperature: 6500K
- Colour rendering index: CRI > 80
- Light colour: 865
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 60W

#### Operating device:

- Control: DALI 2

#### Certificates, Standards

- Protection rating: IP20
- Protection rating (lamp compartment, on room side): IP50
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC

#### Material, Colour

- housing: aluminium, coated, pure white
- Colour specification: pure white
- housing upper side: sheet steel, galvanised
- Cover: micro prismatic cover

#### Mounting

- Mounting method, mounting location: lay-in mounting, in the ceiling
- Arrangement: single arrangement

#### Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 1545mm
- Width: 307mm
- Height: 48mm
- Weight: 3.7kg

#### Service life

- Rated service life: 50000h (L85/B50) at AT = 25°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -