

Order No.: 51LP327DM10AF | **GTIN (EAN):** 4058352704936


Product description: Btn41F,1000lm830/840/850,0/1,PC,sr



Batten 41-F, batten luminaire, primary optical cover: cover, of PC, frosted, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 1.000lm, luminous efficacy: 120lm/W, light colour: 830/840/850, colour temperature: 3000/4000/5000K, control gear: ECG, with terminal, 2-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 8.3W, housing, of aluminium, silver, length: 580mm, width: 25mm, height: 44mm, end cap, of PC, white, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible operating ambient temperature: -20..+40°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.3
GTIN (EAN):	4058352704936



Order No.: 51LP327DM10AF | **GTIN (EAN):** 4058352704936

Detailed technical description: Btn41F,1000lm830/840/850,0/1,PC,sr



Key data

- Product type: batten luminaire
- Product name: Batten 41-F
- Order No.: 51LP327DM10AF

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: cover, frosted
- Beam angle: diffuse distribution
- Symmetry: symmetric
- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 1000lm
- Luminous efficacy: 120lm/W
- Colour temperature: 3000/4000/5000K
- Colour rendering index: CRI > 80
- Light colour: 830/840/850
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 5 SDCM (initial)
- Rated input power: 8.3W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour

- housing: aluminium, silver
- Colour specification: silver
- end cap: PC, white
- Colour specification: white
- Cover: cover of PC

Mounting

- Mounting method, mounting location: surface-mounted
- Arrangement: single/continuous arrangement

Electrical connection

- Connection: terminal, 2-pole
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 580mm
- Width: 25mm
- Height: 44mm
- Weight: 0.3kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51LP327DM10AF | GTIN (EAN): 4058352704936

Dimensions: Btn41F,1000lm830/840/850,0/1,PC,sr

