

Order No.: 51SF12MAD4B | **GTIN (EAN):** 4058352721070

Product description: Spot31,21°,4930lm940,ML,90,wh



Spot 31, directional spotlight, light control with lens, of PMMA, LED rated luminous flux: 4.930lm, light colour: 940, control gear: ECG Multilumen, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, of aluminium, traffic white (RAL 9016), length: 213mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, permissible ambient temperature for indoor applications: -20..+40°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.8
GTIN (EAN):	4058352721070



Order No.: 51SF12MAD4B | **GTIN (EAN):** 4058352721070

Detailed technical description: Spot31,21°,4930lm940,ML,90,wh



Key data

- Product type: directional spotlight
- Product name: Spot 31
- Order No.: 51SF12MAD4B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of PMMA
- Beam angle: 21°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis: ≤ 16
- UGR viewing direction along lateral luminaire axis: ≤ 16

Lamps:

- Lamps: with LED
- Rated luminous flux: 4930lm
- Luminous efficacy: 123lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 40W

Operating device:

- Control gear: ECG Multilumen
- Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour

- Colour specification: traffic white (RAL 9016)

Mounting

- Mounting method, mounting location: slip-in mounting, in a 3-phase track

Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 213mm
- Diameter: 90mm
- Weight: 0.8kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SF12MAD4B | GTIN (EAN): 4058352721070

Dimensions: Spot31,21°,4930lm940,ML,90,wh

