

# Order No.: 51SF337FA2B | GTIN (EAN): 4058352746271

# Product description: Spot31SI,36°,2150lm927,0/1,bk




Spot 31 Slim, directional spotlight, light control with reflector, of aluminium, LED rated luminous flux: 2.150lm, light colour: 927, control gear: ECG, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, housing, of aluminium, jet black (RAL 9005), diameter: 70mm, adapter, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, packaging unit: 1 piece

IP 20 ⊕ (∈

Lamps: LED Wt. (kg): 0.7

GTIN (EAN): 4058352746271





Order No.: 51SF337FA2B | GTIN (EAN): 4058352746271

Detailed technical description: Spot31SI,36°,2150lm927,0/1,bk



# Key data

Product type: directional spotlight

- Product name: Spot 31 Slim

- Order No.: 51SF337FA2B

# Lighting technology | Lamps | Control gear

# Component 1

### Lighting technology:

- Light control: reflector of aluminium

Beam angle: 36°

- Symmetry: symmetric

 UGR viewing direction along longitudinal luminaire axis: ≤ 25

 UGR viewing direction along lateral luminaire axis: ≤ 25

## Lamps:

- Lamps: with LED

- Rated luminous flux: 2150lm

- Luminous efficacy: 126lm/W

- Colour temperature: 2700K

- Colour rendering index: CRI > 90

- Light colour: 927

 SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)

- Rated input power: 17W

# Operating device:

- Control gear: ECG

- Control: ON/OFF

# Certificates, Standards

- Protection rating: IP20

 Insulation class: insulation class I (protective earthing)

- Impact resistance: IK02

- Certification, designation: CE

#### Material, Colour

 housing: aluminium, jet black (RAL 9005)

 Colour specification: jet black (RAL 9005)

adapter: plastic

# **Electrical connection**

- Connection: 3-phase adapter

 Nominal voltage: 220..240V, 50/60Hz, AC

# **Dimensions, Weight**

Diameter: 70mm

- Weight: 0.7kg

#### Service life

 Rated service life: 50000h (L80/B50) at AT = 25°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 51SF337FA2B | GTIN (EAN): 4058352746271

**Dimensions:** Spot31Sl,36°,2150lm927,0/1,bk

