

**Order No.:** 5XA5405JF04F | **GTIN (EAN):** 4058352633540

**Product description:** Mod540iQ,PL1.2s,3110lm730,SR,wh



electrics components group, for Module 540 iQ, gear tray, control gear: ECG iQ, LED luminous flux: 3.110 lm, colour temperature: 3000K, with terminal, 6-pole, max. 2.5mm<sup>2</sup>, mains connection: 230..240V, AC, 50/60Hz, start of lifetime: 19 W, end of service life: 21 W, reduction: 10 W, primary light characteristic: symmetric, width: 190 mm, height: 514mm, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE



Lamps:	LED
Wt. (kg):	2.7
GTIN (EAN):	4058352633540



**Order No.:** 5XA5405JF04F | **GTIN (EAN):** 4058352633540

**Detailed technical description:** Mod540iQ,PL1.2s,3110lm730,SR,wh



#### Key data

- Product type: electrics components group
- Product name: Module 540 iQ
- Order No.: 5XA5405JF04F

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated, highly specular
- Light distribution: PL1.2s
- Beam angle: wide distribution
- Symmetry: symmetric distribution

#### Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 3110lm
- Luminous efficacy: 161lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 5 SDCM (initial)
- Rated input power begin service life: 19
- Rated input power end service life: 21
- Rated input power at 50% lumin. flux: 10

#### Operating device:

- Control gear: ECG iQ
- Control: iQ Street-Remote
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, presetting dimming logarithmic

#### Certificates, Standards

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

#### Material, Colour

- Colour specification: traffic white (RAL 9016)

#### Electrical connection

- Connection: terminal, 6-pole, max. 2.5mm<sup>2</sup>
- Nominal voltage: 230..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

#### Dimensions, Weight

- Width: 190mm
- Height: 514mm
- Weight: 2.7kg

Order No.: 5XA5405JF04F | GTIN (EAN): 4058352633540

Dimensions: Mod540iQ,PL1.2s,3110lm730,SR,wh

