

# Order No.: 5XMOD0114F | GTIN (EAN): 4050737957166 Product description: SL10mc,LEDmod,P1.0a,830

Streetlight 10 micro, LED module, light distribution: P1.0a, primary light characteristic: asymmetric, High Power LED, light colour: 830, colour temperature: 3000K, mains connection: 230..240V, 50Hz, LED module, length: 174mm, width: 137mm, height: 40mm, protection rating (complete): as luminaire, packaging unit: 1 piece

Wt. (kg): 0.6 GTIN (EAN): 4050737957166

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 15.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -



# Order No.: 5XMOD0114F | GTIN (EAN): 4050737957166 Detailed technical description: SL10mc,LEDmod,P1.0a,830

## Key data

- Product type: LED module
- Product name: Streetlight 10 micro
- Order No.: 5XMOD0114F

# Lighting technology | Lamps | Control gear

# Component 1

# Lighting technology:

- Light distribution: P1.0a
- Beam angle: extremely wide
  - distribution
- Symmetry: asymmetric distribution

## Lamps:

- Lamps: with High Power LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830

#### **Certificates, Standards**

- Protection rating: as luminaire

**Electrical connection** 

- Nominal voltage: 230..240V, 50Hz

# **Dimensions, Weight**

- Length: 174mm
- Width: 137mm
- Height: 40mm
- Weight: 0.6kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 15.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -