

Order No.: 5XMOD0175L | GTIN (EAN): 4058352780619 Product description: SL10mc,LEDmod,P1.0a,718



Streetlight 10 micro, LED module, primary light control with cycle path optic, light distribution: P1.0a, primary light characteristic: asymmetric, High Power LED, light colour: 718, colour temperature: 1800K, mains connection: 230..240V, 50Hz, LED module, length: 174mm, width: 137mm, height: 40mm, protection rating (complete): as luminaire, packaging unit: 1 piece


Wt. (kg): 0.8 GTIN (EAN): 40583

0.8 4058352780619

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 17.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5XMOD0175L | GTIN (EAN): 4058352780619 Detailed technical description: SL10mc,LEDmod,P1.0a,718



Key data

- Product type: LED module
- Product name: Streetlight 10 micro
- Order No.: 5XMOD0175L

Lighting technology | Lamps | Control gear

Component 1

- Lighting technology:
- Light control: cycle path optic
- Light distribution: P1.0a
- Beam angle: extremely wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with High Power LED
- Colour temperature: 1800K
- Colour rendering index: CRI > 70
- Light colour: 718
- Supplement: power consumption when used in Streetlight 10 Plus luminaires: construction size micro 11.5..15.8W

Certificates, Standards

- Protection rating: as luminaire

Electrical connection

- Nominal voltage: 230..240V, 50Hz

Dimensions, Weight

- Length: 174mm
- Width: 137mm
- Height: 40mm
- Weight: 0.8kg