

Order No.: 51SL32DA43B | GTIN (EAN): 4058352864913

Product description: LicSp31,21°,3650lm940,DA,bk



Licross® Spot 31, directional spotlight, light control with lens, of plastic, LED rated luminous flux: 3.650lm, light colour: 940, control gear: ECG DALI, with plug, 5-pole, mains connection: 220..240V, AC, 50/60Hz, of aluminium, jet black (RAL 9005), length: 140mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 20  

| | |
|-------------|---------------|
| Lamps: | LED |
| Wt. (kg): | 1.2 |
| GTIN (EAN): | 4058352864913 |



Order No.: 51SL32DA43B | GTIN (EAN): 4058352864913

Detailed technical description: LicSp31,21°,3650lm940,DA,bk



Key data

- Product type: directional spotlight
- Product name: Licross® Spot 31
- Order No.: 51SL32DA43B

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Beam angle: 21°
- Symmetry: symmetric

Lamps:

- Lamps: with LED
- Rated luminous flux: 3650lm
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 28.6W

Operating device:

- Control gear: ECG DALI
- Control: DALI

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- Colour specification: jet black (RAL 9005)

Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail

Electrical connection

- Connection: plug, 5-pole
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 140mm
- Diameter: 90mm
- Height: 116mm
- Weight: 1.2kg

Order No.: 51SL32DA43B | GTIN (EAN): 4058352864913

Dimensions: LicSp31,21°,3650lm940,DA,bk

