


Order No.: 5XCMOD2E3HC | GTIN (EAN): 4058352392126 Product description: SL11,Plusmnmd,LEDmod,PCL,830



Streetlight SL 11 Plus mini/midi, LED module, light distribution: PC-L, primary light characteristic: asymmetric, left, High Power LED, light colour: 830, colour temperature: 3000K, mains connection: 230V, 50Hz, LED module, protection rating (complete): as luminaire, packaging unit: 1 piece

Wt. (kg): 0.6 GTIN (EAN): 4058352392126

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 10.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5XCMOD2E3HC | GTIN (EAN): 4058352392126 Detailed technical description: SL11,Plusmnmd,LEDmod,PCL,830



Key data

- Product type: LED module
- Product name: Streetlight SL 11 Plus mini/midi
- Order No.: 5XCMOD2E3HC

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light distribution: PC-L
- Beam angle: wide distribution
- Symmetry: asymmetric, left

Lamps:

- Lamps: with High Power LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830

Certificates, Standards

- Protection rating: as luminaire
- **Electrical connection**
- Nominal voltage: 230V, 50Hz

Dimensions, Weight

- Weight: 0.6kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 10.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -