

# Order No.: 5EA3NAS01 | GTIN (EAN): 4058352812969 Product description: SConWi,SmartPlugLoRaWAN



SITECO Connect WirelessSmart Plug LoRaWAN, radio, The LoRaWAN key is included in the individual packaging, Smart Interface below and above, installation type: screw fastening, installation location: to the luminaire, of ABS, voltage: 12..20V, voltage type: DC, LoRaWAN, D4i, remote setup and operation, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 (E

Wt. (kg): 0.1 GTIN (EAN): 405

4058352812969

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 22.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -



## Order No.: 5EA3NAS01 | GTIN (EAN): 4058352812969 Detailed technical description: SConWi,SmartPlugLoRaWAN



#### Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA3NAS01

# Lighting technology | Lamps | Control gear

#### **Component 1**

### **Operating device:**

 Control: D4i, Smart Interface below and above, The LoRaWAN key is included in the individual packaging

### **Certificates, Standards**

- Protection rating: IP66
- Temperature range (operation): -30..+60°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: ABS, grey
- Colour specification: grey

## Mounting

 Mounting method, mounting location: screw fastening, to the luminaire

#### **Electrical connection**

- Nominal voltage: 12..20V, DC

#### Dimensions, Weight

Weight: 0.1kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 22.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -