

# Order No.: 59US1FAMA | GTIN (EAN): 4058352363737 Product description: SConbasemod,surf



SITECO ConnectExternal Interface MS, master, local control, switchable, installation type: surface-mounted, installation location: to the ceiling, to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, VDE, voltage: 230V, voltage type: AC, packaging unit: 1 piece

▶ IP 54 □ CE

Wt. (kg): 0.1 GTIN (EAN): 405

0.1 4058352363737

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 16.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

# ѕітесо

# Order No.: 59US1FAMA | GTIN (EAN): 4058352363737 Detailed technical description: SConbasemod,surf

## Key data

- System family: SITECO Connect 31 Logistic On/Off
- Product type: base module
- Product name: SITECO Connect
- Order No.: 59US1FAMA

## Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, VDE

#### Material, Colour

- housing: plastic, white, square
- Colour specification: white

#### Mounting

 Mounting method, mounting location: surface-mounted, to the ceiling, to the luminaire

#### **Electrical connection**

- Nominal voltage: 230V, 50Hz, AC

### **Dimensions, Weight**

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.1kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 16.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

