

Order No.: 5EA3BGH02 | **GTIN (EAN):** 4069025002723

Product description: SConWi,MastBoxMot2PIRGPSHigh



SITECO Connect WirelessMast Box Motion 2xPIR GPS High, installation type: surface-mounted, installation location: to mast, of plastic, voltage: 230V, voltage type: AC, 2.4GHz, local mesh radio network, DALI, local setting and operation with USB stick, by movement, optionally via radio push button, by time, by timer, by weekday, with radio clock, 2 PIR movement sensors, GPS, GPS, radio, 2.4GHz, protection rating (complete): IP65, certification: CE, packaging unit: 1 piece

IP 65 CE

Wt. (kg): 0.8
GTIN (EAN): 4069025002723

Order No.: 5EA3BGH02 | GTIN (EAN): 4069025002723

Detailed technical description: SConWi,MastBoxMot2PIRGPSHigh



Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA3BGH02

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI

Certificates, Standards

- Protection rating: IP65
- Temperature range (operation): -25..+80°C
- Certification, designation: CE

Material, Colour

- housing: plastic, dark grey
- Colour specification: dark grey

Mounting

- Mounting method, mounting location: surface-mounted, to mast
- Mounting height: 6..12m

Electrical connection

- Nominal voltage: 230V, AC

Dimensions, Weight


- Weight: 0.8kg

Order No.: 5EA3BGH02 | GTIN (EAN): 4069025002723


Dimensions: SConWi,MastBoxMot2PIRGPSHigh

Detection zone "Mast Box Motion"
5EA3BGH02

Side view



Top view



Mounting height	X axis	Y axis
5.0 - 12.0m	22.0 m	14.0 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 12.04.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -